

Konte Nogqi

XGRIP N09QI Pneumatic Powered Blind Rivet Nut Tool







XGRIP N09QI

Pneumatic Powered Blind Rivet Nut Tool

The Masterfix range of hydraulic/pneumatic XGRIP tools was developed with an emphasis on reliability, ergonomics, and continuous operations.

The XGRIP N09QI is equipped with a quick interchange system, meaning without any instruments the conversion kits can be changed. Other notable features include a pressure regulation system to ensure a correct setting of the nuts/studs, and automatic right and left-hand air connection for quick and easy setting.

Fast facts:

- Hydraulic/pneumatic blind riveting power tool.
- Ergonomic design.
- No key needed, utilizes the Masterfix quick interchange system.
- Masterfix power tools meet the current CE-standard.

This tool is designed for riveting with:

- Rivet nuts M3-M12 (aluminium, steel, stainless steel)
- Rivet studs M4-M8 (aluminium, steel, stainless Steel)

Equipment included: Conversion kit blind rivet nuts M4 – M10



Part number: • T45209N09QI

Specifications

Pull Force (Kn [Lb])	23.0 [5,170.6]	
Placing Stroke - (Mm [In])	8.0 [0.315]	
Power Source	Air	
Working Pressure (Min/Max)	5.0 Bar	7.0 Bar
Tool Weight (Kg [Lb])	2.0 [4.4]	
Tool Dimensions L X H - (Mm	270 x 262	
[In])	[10.6 x 10.3]	
Air Consumption (L/Stroke)	1.5	
Sound Level	68.6 dB(A)	
Sound Pressure	68.6 dB(A)	
Vibration Level	< 2.5 m/s ² [8 ft/s ²]	
Compliance Standards	Safety: CE	
Operating Modes	Pull to stroke	
	Pull to force	
Operating Temperature	+5°C - +40°C	
Operating Humidity:	Up to 70%	

Placing Capacity

Material	Minimum Size	Maximum Size
Aluminium	M3	M12
Steel	M3	M12
Stainless Steel	M3	M12

Typical General Industrial Applications:

- Heating Ventilation & Air Conditioning (HVAC) applications
- Lighting applications
- Domestic appliances

Typical Transportation Applications:

- Seating and passenger safety applications
- Trailer, bus, and coach ancillaries applications

For more information, please contact our team of specialists at www.stanleyengineeredfastening.com