# SPECIAL 20 WORLDWIDE









### New extra deep tool trolley 179NXXL-8D



### **Upgrade for the tool trolley**



### **Lateral door (optional)**

- · Lateral door, lockable
- · Cable opening in the door (above and
- For left or right side panel on 179 NXXL-8D
- Including 2 keys

### Made in Germany 179N-21D EAN-No. 4000896245154





### **Socket strip** (optional)

- Can be integrated in the right side
- Toggle switch for deactivating the power supply
- Integrated 3-way protective earth socket strip 230 V, 50/60 Hz
- 4 USB ports (4x 2.1 A)
- Cable length: 190 cm





### Tool trolley 179NXXL-8D/619 with 616 expert tools, lateral door and socket strip



**NEW!** 

Including

Assortment



- · Much larger storage and work areas made from stainless steel
- 7 flat drawers (81 x 870 x 522 mm) and 1 high drawer (166 x 870 x 522 mm)
- 100% drawer slide-out with ball-bearing telescopic slides
- Loading capacity per drawer: 40 kg









163D-3/94 







163D-5/24 ○ ○ ●

163D-4/44 125 1/2 📵 🕦 🔾


163D-2/103

10 % 10 % 18 10 10




163D-12/30





● s 6x7 – 36x41 mm

163D-7/24 **⊕ ⊙ ⊙** 



163D-11/11









163D-6/53 **● ○** ○ ○ ○



163D-8/13



HAZET No.	HAZET Designation		Number of drawers	4	EAN-No. 4000896+	
179NXXL-8D	Tool trolley without assortment	Stainless steel	8	1	242931	
179NXXL-8D/3	79NXXL-8D/3 Tool trolley with lateral door and socket strip (without assortment)		8	3	245178	
179NXXL-8D/619	Tool trolley with assortment, lateral door and socket strip	Stainless steel	8	619	245185	



### Tool trolley 179NXXL-7/340 with 340 expert tools









Stainless steel Work surface Rost



179NXXL-7 Made in Germany  $H \times W \times D$ 1,020 x 1,133 x 518 mm



With stainless steel work surface

179NXXL-7/340

EAN-No. 4000896**215072** 





163-480/57 € ○ ○ ○









2128N-1





163-509/12



#### **Tool trolley without assortment**

- Stainless steel work surface
- Total loading capacity: 1,000 kg (static) / 750 kg (dynamic)
- Drawer loading capacity: 40 kg each
- Drawer slide-out: 100%
- Dead weight: 145 kg
- Drawer internal dimensions: 870 x 398 mm

#### Made in Germany

made in definally					
HAZET No.	Number of drawers				
179NXXL-7	7				
179NXXL-8	8				


# Tool trolley 179NXL-8/321 with 321 expert tools!



















179NXL-8

Made in Germany

H x W x D

1,020 x 959 x 518 mm

With stainless steel work surface 179NXL-8/321

EAN-No. 4000896224395







163-480/57 🗢 🗘 ○ ○




163-479/26

163-478/40 🗇



#### 163-522x50



#### **Tool trolley without assortment**

- Stainless steel work surface
- Total loading capacity: 1,000 kg (static) / 750 kg (dynamic)
- Drawer loading capacity: 40 kg each
- Drawer slide-out: 100%
- Dead weight: 125 kg
- Drawer internal dimensions: 696 x 398 mm

#### 💳 Made in Germany

HAZET No.	Colour	Number of drawers					
179NXL-6		6					
179NXL-7		7					
179NXL-8		8					
179NXL-8-VW		8					



# Tool trolley 179NX-7 / 179N-7 with 137 expert tools



### Two trolleys to choose from – each with the same assortment!









### Tool trolley 179N-7 with 220 expert tools














163-138/77 🕲 🔾 🗘 🗘 😂 125 1/2 6.3 1/4





With plastic work surface 179N-7/220 EAN-No. 4000896220267



163-141/31 🗢 🔾 🔾 🔾







2128N-1



#### Made in Germany

HAZET No.	Colour	Work surface	Number of drawers
179N-6		Plastic	6
179N-7		Plastic	7
179N-7-RAL3020		Plastic	7
179N-7-RAL9005		Plastic	7
179N-8		Plastic	8
179N-8-RAL7021		Plastic	8
179NX-6		Stainless steel	6
179NX-7		Stainless steel	7
179NX-7-RAL3020		Stainless steel	7
179NX-8		Stainless steel	8

#### **Tool trolleys without assortment**

- Stainless steel or plastic work surface
- Total loading capacity: 1,000 kg (static) / 540 kg (dynamic)
- Drawer loading capacity: 25 kg each, drawer opening: 100%
- Dead weight: 90 kg
- Drawer internal dimensions: 522 x 398 mm









# Tool trolley 178N-7/204 with 204 expert tools

# Assistent®



6.3 1/4" 10 3/8" 125 1/2"







178N-7

Made in Germany

H x W x D


1,037 x 781 x 498 mm

**178N-7/204** EAN-No. 4000896228072




















2128N-1

#### Tool trolley / tool chest without assortment

- Plastic work surface
- Total loading capacity: 480 kg (static) / 480 kg (dynamic)
- Drawer loading capacity: 20 kg each
- Drawer slide-out: 100%
- Dead weight: trolley 74.1 kg / tool chest 33.7 kg
- Drawer internal dimensions: 527 x 348 mm

#### Made in Germany

HAZET No.	Number of drawers
178N-7	7
178N-10	10
178NK-3	3







178NK-3 H x W x D 390 x **696** x 488 mm

### Work bench 179NW-7/230 with 230 expert tools
















179NW-7 Made in Germany HxWxD 964 x 1,150 x 600 mm

179NW-7/230 EAN-No. 4000896219605













#### Work bench without assortment

- Wood multiplex birch work surface
- Total loading capacity: 1,000 kg (static) / 750 kg (dynamic)
  Drawer loading capacity: 25 kg each, bottom drawer 40 kg
- Drawer slide-out: 100%
- Dead weight: 120 kg

#### Made in Germany

HAZET No.	Number of drawers
179NW-7	7



- · Drawer internal dimensions: 522 x 398 mm
- · Includes fixed mounted door. Only one lock for door and drawers
- Flexible vice assembly (front, right, left) e.g. HAZET 2175N according to drilling template specification
- · Cable duct on rear panel allows battery devices to be charged when the door is closed, for instance





### Tool trolley / work bench accessories L-Boxx bracket

### Tool trolley / work bench accessories

HAZET No.	Designation	Tool catalogue 2022
179N-33	Paper bin incl. holder	Page 49
161N-3D/2	Cable drum incl. holder	Page 47
161N-3D	Cable drum (without holder)	Page 47
179N-45	Tray holder	Page 50
179N-35	Can holder	Page 49
179N-46	Impact wrench holder	www.hazet.de
179NW-11	Machinist's vice fastening set	www.hazet.de
179N-42	Laptop holder for 179N · 179NX · 179NXL · 179NXXL	Page 49
179-35	Can holder	Page 48
180-24	Document holder	Page 51

HAZET No.	Designation	Tool catalogue 2022
179N-21	Lateral door for 179N · 179NX · 179NXL · 179NXXL	Page 49
180-34	Holder for paper reel	Page 51
179N-19	Small parts collector	Page 49
179 N-26	Perforated tool panel for 179N · 179NX	Page 49
179N-75	Vice fastening for machinist's vice 2175N	Page 50
179N XL-26	Perforated tool panel for 179 NXL	Page 50
179N XXL-26	Perforated tool panel for 179NXXL	Page 50
179N-21D	Lateral door for 179NXXL-8D	SWW page 2
161N-5D	Socket strip for 179NXXL-8D	SWW page 2

More information in the 2022 tool catalogue from page 47



#### L-Boxx bracket for lateral installation on tool trolleys

• Maximum load per L-Boxx: 15 kg







L-Boxx brackets mounted to the trolley for illustration. Delivery without trolley and L-Boxx.













#### Bracket for one L-Boxx

- · For attachment to tool trolleys 179N · 179NX · 179NXL · 179NXXL · 179NW · 179NXXL-8D
- Dimensions: 528 x 144 x 50 mm

#### 179N-50

EAN-No. 4000896243068



#### **Bracket set for two L-Boxxes**

- Bracket with two bracing surfaces
- For attachment to tool trolleys 179 · 179XL · 179XXL · 179N · 179NX · 179NXL · 179NXXL · 179NXXL-8D · 179NW
- Optionally extendable with 179 N-510 for three L-Boxxes
- Dimensions: 515 x 441 x 496 mm
- Contents:
- 1x bracket
- 2x bracing surfaces (179 N-510)

#### 179N-51

EAN-No. 4000896243051

#### **Bracing surface for L-Boxx bracket** 179 N-51

- Bracing surface for installing a third L-Boxx on L-Boxx bracket 179 N-51
- Installation only on tool trolleys 179 XL · 179 XXL · 179 N XL · 179 N XXL · 179 N W · 179 N XXL-8D
- Dimensions: 441 x 409 x 86 mm

#### 179N-510

EAN-No. 4000896243075



### L-Boxx

#### **L-Boxx** – The tool case

- Patented click system connects the L-Boxx to other L-Boxxes easily and reliably
- Storage and transport of high-quality tools
   Extremely robust due to impact and shock resistant ABS plastic
- Cover loading capacity: up to 100 kg
- Loading capacity of the carrying handles (loading content): 25 kg
  Ergonomic transport handles on head and side panels
- With labeling fields
- Dirt repellent and easy to clean








190L-102

190L-136

HAZET No.	External dimensions mm L x W x H	Internal dimensions mm L x W x H	Volume (litres)	<b>∆</b> <sup>t</sup> <b>∆</b> <sub>kg</sub>	EAN-No. 4000896+	
190L-102	445 x 358 x 118	378 x 313 x 65	8.8	2.1	237609	
190L-136	445 x 358 x 152	378 x 310 x 101	13.3	2.2	237616	





**NEW!** 

**Tool set in L-Boxx** 

























# **HAZET tools for craftsmen,** industry and automotive repair



### **SCAN QR-CODE NOW** AND DISCOVER MORE INFORMATION, **VIDEOS AND APPLICATIONS!**

www.hazet.de/smartcase

REALITY










Innovative concept of a compact, foldable tool set



Overview of contents using icons, quick recognition of the set content



Can be folded flat or stood up (similar to a tablet case)



1/4" screwdriver bit and offset screwdriver set, 69 pieces, 130 mm





















0.4 x 1.5 mm Incl. small screwdriver bit (slot) for e.g. glasses repair

2200SC-1 EAN-No. 4000896239252



### **SmartCase**

### 1/4" socket and screwdriver bit set, 50 pieces, 130 mm















2200SC-2 EAN-No. 4000896**239603** 
















000000 C++++





SMPRT EMSE
DESIGNED & PRODUCED
IN GERMANY








Available in April 2022!





### **SmartCase**



1/4" screwdriver bit and offset screwdriver set,  $TORX^{\circledR}$  inside hexagon, 73 pieces, 210 mm









6.3 1/4"







63 1/4 63 1/4 6.3 1/4 🔷 🔷 🗘 🔘 🕲

Available in April 2022!

**2200SC-31**EAN-No. 4000896244539

1/4" screwdriver bit and offset screwdriver set, 59 pieces, 210 mm















Available in April 2022!

**2200SC-32**EAN-No. 4000896244546








THE NEW SMARTRAIL PRODUCT WORLD ...

### **SCAN OR-CODE NOW** AND DISCOVER MORE INFORMATION, **VIDEOS AND APPLICATIONS!**

www.hazet.de/smartrail





- Magnetic underside ensures perfect hold on all magnetic surfaces, e.g. tool trolleys, tool walls, machines, lifting platforms and in drawers
- Flexible plastic connector strip with 1/2" square slots
  Easy to clean material and pleasant surface feel
- · Durable, robust twist lock for a tight fit and instant access
- More securely fixed when locked: turn socket left to remove
- Incl. robust metal lug for hanging, e.g. on a hook





SmartRail available for holding 5 or 8 sockets



900SR-5

EAN-No. 4000896244508



• Dimensions: L: 245 x W: 37.4 x H: 29.2 mm



#### 900SR-8

EAN-No. 4000896244515



**SmartRail with 8 slots** 

• Dimensions: L: 365 x W: 37.4 x H: 29.2 mm

#### SmartRail socket sets (5 pieces)

#### 1/2" hexagon, short

- s 10 · 13 · 17 · 19 · 22 mm
- · Length: 38 mm





· Length: 85 mm















900-SR/5



To 125 1/2"





900LG-SR/5 EAN-No. 4000896245246



### 1/2" impact socket, short

- · Length: 38 mm




Made in Germany 900S-SR/5

EAN-No. 4000896**245260** 



#### 1/2" impact socket, long

- s 13 · 17 · 19 · 22 · 24 mm
- Length: 85 mm



Made in Germany 900SLG-SR/5 EAN-No. 4000896**245277** 



#### 1/2" impact socket with rim guard

- s 17 (3x) · 19 (2x) mm
- Length: 85 mm















EAN-No. 4000896245253



### **SmartRail**

#### 1/2" 12-point, short

- s 10 · 13 · 17 · 19 · 22 mm
- Length: 38 mm (s 22: 41.5 mm)



- 1/2" TORX®, short • s T30 · T40 · T45 · T50 · T55
- Length: 55 mm (T55: 56 mm)





- s E12 · E14 · E16 · E18 · E20
- · Length: 38 mm








Made in Germany 900Z-SR/5

EAN-No. 4000896245291





Made in Germany 992T-SR/5

EAN-No. 4000896245307





Made in Germany 900E-SR/5

EAN-No. 4000896245314






#### 1/2" serration, short

- s M6 · M8 · M10 · M12 · M14
- Length: M6: 52 mm / M8-M10: 53 mm / M14: 58 mm



- 1/2" inside hexagon, short
- s 5 · 6 · 7 · 8 · 10 mm · Length: 60 mm





• s 12 · 14 · 17 · 19 · 22 mm









Made in Germany 990-SR/5

EAN-No. 4000896245284







Made in Germanv 986K-SR/5 EAN-No. 4000896245321



Made in Germanv 986G-SR/5





### SmartRail socket sets (8 pieces)

#### 1/2" hexagon, short



• s 10 · 13 · 16 · 17 · 18 · 19 · 22 · 24 mm

• Length: 38 mm (s 22: 41.5 mm / s 24: 44 mm)



1/2" impact socket set, short

• s 13 · 17 · 18 · 19 · 21 · 22 · 24 · 27 mm







Made in Germany





• Length: 38 mm (s 19-22: 40 mm / s 24: 44 mm / 8 s 27: 45 mm)




125 1/2

• s M5 · M6 · M8 · M10 · M12 · M14 · M16 · M18 Length: M5-M6: 52 mm / M8-M10: 53 mm /

M12: 55 mm / M14: 58 mm / M16: 60 mm / M18: 85 mm









#### 1/2" TORX®, short



Made in Germany

EAN-No. 4000896245345

900S-SR/8



#### 1/2" E-TORX®, short



- s6·7·8·9·10·12·14·17 mm
- · Length: 60 mm




- s T20 · T25 · T30 · T40 · T45 · T50 · T55 · T60
- Length: 55 mm (T55-T60: 56 mm)












Made in Germany 986-SR/8

EAN-No. 4000896245390










#### Made in Germany 992T-SR/8

EAN-No. 4000896245376









### Screwdriver bit sets | Ratcheting bit screwdriver





Bit adapter

Push button to open the

magazine

### 1/4" ratcheting bit screwdriver with built-in magazine

- Ratchet function is convertible or for use as normal screwdriver
- · Bit magazine is easy to open by pressing a button while pulling
- · Comfortable to hold, offers effective impact
- · Length: 170 mm (closed, without extension)



810R-3 EAN-No. 4000896239658



### 1/4" ratcheting bit screwdriver set

- Ratcheting bit screwdriver 810R-1
- Extension 810R-2
- 12x bits

=	) P	<b>68</b> 14ï	0.5 x 4.0 · 1.2 x 6.5 mm
0	<b>—</b>	<b>®</b> ₩	PH 1 · PH 2
0	- D	<b>®</b> ₩	PZ 1 · PZ 2
0		<b>®</b> ₩	s 4 · 5 · 6 mm
0		<b>®</b> ₩	T15 · T20 · T25

### 1/4" ratcheting bit screwdriver set

- Ratcheting bit screwdriver 810R-1
- Extension 810R-2
- 12x bits



EAN-No. 4000896239665

810R-4

<b>=</b>	3 2 -w	€9 147	0.8 x 5.5 mm
0	~	€9 147	PH 2 · PH 3
0		₩ ₩	s 3 · 4 · 5 · 6 mm
0		683 1/4"	T15 · T20 · T25 · T27 · T30







HAZET No.	Designation	Bayonet fitting	[ mm	EAN-No. 4000896+	
810BHK	Bit holder	1	98	237579	
2239N-6	Bit adapter	1	60	238934	

### Screwdriver sets **Pliers**











0

PH1·PH2


### Universal pliers with quick-adjust lever

- Comfortable quick adjustment thanks to tip/step lever function
- Adjustment without re-gripping one-hand actuation possible



#### Made in Germany

HAZET	[	EAN-No.	
No.	mm	4000896+	
760-2	260	188451	







THE NEW HIPER PRODUCT WORLD ...

### SCAN QR-CODE NOW AND DISCOVER MORE INFORMATION, VIDEOS AND APPLICATIONS!

www.hazet.de/hiper



#### **HiPer – Our classics**

- A lot more power than with ratchets of the same dimensions
- HAZET internal quality standards guarantee loading capacity far beyond standard requirements
- 90 teeth, 4° fine toothed for confined spaces
- · Locking function of the lever prevents unwanted switch
- Surface: chrome-plated, polished

#### Made in Germany

H <u>AZET</u> No.		Nm	/ mm	EAN-No. 4000896+	
863HPB	6.3 1/4	120	116	235346	
863HP	6.3 1/4"	120	116	226917	
8816HP	10 3/8	400	200	235063	
916HP	125 1/2	1,000	275	213894	
916HPL	125 1/2	1,000	415	219209	
916HPLG	125 1/2	1,000	414 – 614	233076	

"Carpenters often do not work in workshops, but rather outdoors. Robust tools should be able to withstand these tougher conditions!"


Holger and Lena



# 1/2" HiPer – fine-tooth reversible ratchet, short

- Short style, only 200 mm, same compact design as a 3/8" ratchet
- Integrated suspension option in the handle
- Locking function of the lever prevents unwanted switch
- Small operating angle (4°) enables use in the tightest of spaces
- Number of teeth: 90
- With locking ball
- For manual operation





HAZET No.		Nm	/ mm	EAN-No. 4000896+	
916HPK	125 1/2	400	200	244379	

### HiPer - with safety locking

- Loosening-proof locking thanks to push button actuation
- Attached tools can easily be released by pressing the button with just one hand







#### Made in Germany

HAZET No.		Nm	/ mm	EAN-No. 4000896+	
863HPS	6.3 1/4"	100	116	237234	
8816HPS	10 3/8"	340	200	237241	
916HPS	125 1/2	850	275	237258	

### Nut-driver | Various hand tools





□ s 10 · 11 · 12 · 13 · 14 · 15 · 16 · 17 · 18 · 19 · 21 · 22 · 24 mm

13

600LG/13



### Tools with 1,000 V protective insulation







**163-542/18** ● s 7 – 32 mm ①

163-172x50





163-226/4

frei 179NX-7-RAL3020 Made in Germany

work surface Rost

163-545/41 10 %





163-229/7 € ♥

**C O G** 

10 <sup>3</sup>⁄8″ 125 1∕2″

#### 179NX-7/70KV

EAN-No. 4000896235483

### High-voltage screwdriver set for electricians, with protective insulation

HxWxD 1,020 x 785 x 518 mm

- · Ergonomically shaped HAZET 2-component handle (red/yellow)
- Voltmeter (839-1), 220-250 V according to DIN VDE 06800-6

7	100
2	


810/6VDE
EAN-No. 4000896179329

•	810VDE	0.4x2.5 · 0.6x3.5 · 0.8x4 mm
•	839-1	0.5x2.8 mm
0	810VDE	PH 1 · PH 2

### High-voltage torque wrench, with protective insulation

- Can be calibrated
- · Long service life / high accuracy
- Option of:- Removal Repair (if necessary) Installation Adjustment Calibration
- Note: adjustment, possible repairs with removal/installation of the KV torque wrench only in the HAZET Service Center
- · Suitable for control of inspection and test equipment
- Sustainable and environmentally sound
- Safe: palpable (close-gap release), audible ("click" sound)
- Right/left release with plug-in square, tightening at torque setting both to the right and to the left within the specified tolerance
- · Low weight for good handling and fatigue-free work
- DIN EN ISO 6789-2:2017, Square according to DIN 3120, ISO 1174-1, IEC 60900:2018

#### Made in Germany





	<b>∆</b> <sup>t</sup> <b>∆</b> <sub>kg</sub>	EAN-No. 4000896+	
	0.59	235421	in the
)	0.64	235445	


# HAZET

### 3/8" high-voltage tool set, with protective insulation

- For all work on HV systems
- Produced according to current DIN specifications
- Optimal protection and highest level of safety thanks to constant quality control
- Delivery in HAZET L-Boxx all tools ready to hand
- Maintenance and repair on passenger cars with electric drives, such as VW · AUDI · BMW · MERCEDES-BENZ · TESLA · TOYOTA etc.
- TIP! For retrofitting: Recess for HAZET 3/8" high-voltage torque wrench 5109KV (5 25 Nm) intended (See page 22)

Universally applicable for all work on high-voltage systems in trade and industry as well as on electric and hybrid vehicles











(2x)

**150/27** EAN-No. 4000896245550

THE NEW 5000-3CT PRODUCT WORLD ...

### SCAN QR-CODE NOW AND DISCOVER MORE INFORMATION, VIDEOS AND APPLICATIONS!

www.hazet.de/5000-3CT

#### **SYSTEM 5000-3CT**

### 1/4" torque wrench with screwdriver bit ratchet

- With @ reversible ratchet for screwdriver bits for particularly limited spaces
- For e.g. maintenance and service work on the burner flange or the electrodes on compact modules for condensing and combi gas boilers
- For two-wheelers, particularly recommended for aluminium and carbon parts as well as for plastic add-on parts or cladding for motorcycles, scooters and bicycles








#### 💳 Made in Germany

HAZET No.	Output	[ mm	<b>Q</b> mm	<i>b</i> mm	Tolerance %	Nm	Ŋ <sup>Nm</sup>		EAN-No. 4000896+	
5107B-3CT	6.3 1/4	234	10.2	24	4	1-9	0.1	0.6-5.5	244584	
5108B-3CT	6.3 1/4	234	10.2	24	3	2.5-25	0.25	1.4-15.3	244591	

#### **Torque wrench with reversible ratchet**

- Recessed zones in the handle ensure optimum force transmission and non-slipping thanks to more grip
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the
  desired torque value by turning the handle
- Safe locking of the setting values by latching function on the blue rotary assembly
- · Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the blue rotary assembly
- Trigonometric shape of the blue rotary assembly prevents uncontrolled rolling away
- Optimised sealing ring to protect against debris
- Accuracy  $\pm$  3% of scale value (in direction of actuation for right-hand tightening) / 5107-3 CT  $\pm$  4% accuracy of scale value
- · Laser lettering of the metallic scale sleeve and scale ensures permanent legibility
- Integrated shift lever with free-running function for the measuring ranges 20 320 Nm reduces the risk of injury and malfunction (5121-3CT, 5122-3CT, 5123-3CT)
- Tested according to DIN EN ISO 6789-2:2017 with calibration certificate and serial number
- Outside square according to DIN 3120, ISO 1174-1
- . Delivery in sturdy Hexa plastic box















#### 💳 Made in Germany

					1					
H <u>AZET</u> No.	Output	<u>l</u> mm	a mm	<b>b</b>	Tolerance %	Nm	<b>∀</b> <sub>Nm</sub>		EAN-No. 4000896+	
5107-3CT	6.3 1/4"	234	10.2	24	4	1-9	0.1	0.6-5.5	218875	
5108-3CT	6.3 1/4"	234	10.2	24	3	2.5-25	0.25	1.4-15.3	218882	
5110-3CT	10 3/8	320	14.5	32	3	10-60	0.5	3.9-25.0	218899	
5111-3CT	10 3/8	375	14.5	32	3	20-120	1	6.9 - 43.5	235384	
5120-3CT	125 1/2	320	14.5	32	3	10-60	0.5	3.9-25.0	218905	
5121-3CT	125 1/2	421	19.6	44	3	20-120	1	6.1-38.0	218912	
5122-3CT	125 1/2	519	19.6	44	3	40-200	1	9.4-49.5	219001	
5123-3CT	125 1/2	628	19.6	44	3	60-320	2	11.3-62.2	218998	
5143-3CT	125 1/2	790	28.5	64	3	100-400	2.5	14.8 - 60.3	235407	
5145-3CT	20 3/4"	1271	28.5	64	3	300-800	2.5	26.2-71.0	218929	

### Torque technology



**SYSTEM 7000 sTAC** 

# martTAC

Made in Germany

**Electronic torque wrench with built-in** angle gauge for highly precise screwing applications with Smart technology -**Ready for Industry 4.0** 

- HAZET Smart Technology consisting of a SmartTAC app and Low Energy Bluetooth Interface
- · Live data exchange for displaying the bolting process on mobile devices
- Programming torque wrenches with built-in angle gauge and documentation of the screw data via laptop and PC with SmartTAC tool 7910-sTAC
- All sTAC torque wrenches with built-in angle gauges can also be used autonomously, without SmartTAC app











#### SmartTAC 100 7910-sTAC

SmartTAC-Tool (7910-sTAC) is the paid programming and analysis software



**Free for Android** and iOS

Simply download in the app store


More information in the tool catalogue 2022, page 296

### DAkkS calibration laboratory - Competence for calibration of torque and rotation angles



- Accredited according to DIN EN ISO/IEC 17025 for measured values:
  - Torque (DIN EN ISO 6789-2:2017)
  - Rotation angle (VDI/VDE 2648 page 2; without item 4.2)
- Complies with special demands of ISO/TS 16949 for calibration laboratories (mandatory requirement for all suppliers of the automotive industry)
- HAZET-owned calibration laboratory guarantees optimal technical calibration competence by accreditation
- Authorised to issue calibration certificates













# TwinTurbo

Technology by HAZET


Twin Effect – More power in shorter time!







\*\* Determined with screw size M16















HAZET No.		Max. Nm	rpm	∆ <sup>1</sup> ∆ kg	I/min	∭∑ dB(A) Lp A	m/s²	S		MD	STO STORES	EAN-No. 4000896+	
9012TT	125 1/2	2,200	8,300	1.6	147.2	99.7	8.69	1	12.91 (1/4")	7.2	1	226924	
9012ATT	125 1/2	550	8,000	1.3	113	90.1	4.89	1	12.91 (1/4")	7.2	1	234738	
9013TT	20 3/4"	4,100	5,200	4.5	243.5	99.5	10.69	1	12.91 (1/4")	7.2	1	227143	

#### Low noise hoses



540

232994

16.41 mm (3/8")





19.21 mm (1/4")

9040-013

### **SCAN QR-CODE NOW** AND DISCOVER MORE INFORMATION, **VIDEOS AND APPLICATIONS!**


www.hazet.de/twinturbo





# Strongest HAZET impact wrench series ever!





HAZET No.		Max. Nm	rpm	∆ <sup>1</sup> ∆ kg	I/min	))) dB(A) Lp A	m/s²	<b>S</b>			an Do	EAN-No. 4000896+	
9013LGTT	20 3/4"	3,800	5,200	5.5	243.5	102.5	9.02	1	16.41 (3/8")	7.2	1	232277	
9014TT	25 <b>1</b> ″	4,100	5,200	4.6	235	101.9	19.11	1	20.67 (1/2")	10	1	234684	
9014LGTT	25 <b>1</b> ″	3,850	4,600	5.9	235	102.5	17.31	1	20.67 (1/2")	10	1	234677	



### Impact wrenches





Top seller!



3/4"
9013M
Max. loosening
torque: 1,890 Nm









Pin clutch mechanism



Single hammer striking mechanism



Twin hammer mechanism



Direct striking mechanism

HAZET No.		Max. Nm	rpm rpm	∆ ∆ kg	I/min	)))) dB(A) Lp A	∭ m/s²	7			<b>0</b> 000	a Tri	am G	<b>E</b> 90	EAN-No. 4000896+	
9011M	10 3/8	461	6,500	1.2	85.2	90.3	7.78	1	12.91 ( <sup>1</sup> / <sub>4</sub> ")	7.2	_	1	_	_	201570	
9012M-1	125 1/2	1,200	8,800	1.3	127.4	92.2	13.49	1	12.91 (1/4")	7.2	_	1	_	_	218356	
9012SPC	125 1/2	850	7,000	2.6	127.4	92.1	7.42	1	12.91 (1/4")	7.2	1	_	-	-	119639	-
9013M	20 3/4"	1890	7,300	2.1	153	104	7.47	1	12.91 (1/4")	7.2	_	-	1	_	212347	

#### Silicone protective covers

HAZET No.	Designation	EAN-No. 4000896+	
9012M-S	Can be used for 9011M and 9012M	202232	
9012M-1-S	Can be used for 9012M-1	222735	
9012SPC-S	Can be used for 9012SPC, 9012-1SPC, 9012 P-1	222476	



### Air ratchet

# HAZET

#### Mini air ratchets


1/4" 9020P-2

- Max. loosening torque: 40 Nm
- For hand retightening with torque values > 60 Nm

3/8" 9021P-2

- Max. loosening torque: 54 Nm
- ullet For hand retightening with torque values > 260 Nm






### **Impact ratchet**

3/8" 9021SR-1

- Max. loosening torque: 68 Nm
- For hand retightening with torque values > 260 Nm












#### Air ratchet

1/2" 9022P-2

- Max. loosening torque: 108 Nm
- For hand retightening with torque values > 400 Nm







### Impact ratchet

1/2" 9022SR-1

- Max. loosening torque: 102 Nm
- For hand retightening with torque values > 270 Nm








### High performance air ratchet

1/2" 9022-360

- Max. loosening torque: 120 Nm
- For hand retightening with torque values > 500 Nm (competitive product: approx. 250 Nm)

Mode	))))) db (A) Lp A	max. Nm
Quiet	81.5	95
Normal	91.2	120





360° rotatable operating lever




### **Extra long air ratchet**

1/2" 9022P-XLG

- Max. loosening torque: 94.8 Nm
- For hand retightening with torque values > 400 Nm







HAZET No.		max. Nm	rpm	<b>∆</b> <sup>1</sup> <b>∆</b> kg	I/min.	))))) db (A) Lp A	M/s²	- Fig			EAN-No. 4000896+	
9020P-2	6.3 1/4"	40	250	0.5	72	90	3.30	1	12.91 (1/4")	7.2	184323	
9021P-2	10 3/8	54	300	0.5	103	92	3.9	1	12.91 ( <sup>1</sup> / <sub>4</sub> ")	7.2	184545	
9021SR-1	10 3/8	68	500	0.7	68	82	9.84	1	12.91 (1/4")	7.2	218295	
9022P-2	125 1/2	108	280	1.2	113	99	9.1	1	12.91 (1/4")	7.2	184538	
9022SR-1	125 1/2	102	400	1.3	113	91	4.53	1	12.91 (1/4")	7.2	170593	
9022-360	125 1/2	120	200	1.5	107.6	91.2	4.87	1	12.91 ( <sup>1</sup> / <sub>4</sub> ")	7.2	209781	
9022P-XLG	125 1/2	94.8	160	2.1	99.12	93.7	5.6	1	12.91 (1/4")	7.2	222513	




### Sander

#### **Belt sander**


- Including three abrasive belts 330 x 10 mm (grain size 80, 100, 120)
- For narrow surfaces (belt width 10 mm)
- Locking device for quick belt changing
- · Continuous speed regulation via speed regulator on back of handle





## Right-angle grinder • For areas with difficult access

- · Lateral handle, to be used on left or right side
- Quick adjustment of protection cover without tools
- For grinding discs 0.8-6 mm thick
- Spindle thread: M 14 x 2





#### Angle grinder

- Suitable for cutting metal sheet and steel
- · Quick adjustment (without tools) of protective cover
- Pressure key for locking the output enables easy changing of cut-off wheels



### Angle grinder

- · For processing workpieces even in areas with very restricted access
- Power: 522 watts
- Including 1 cut-off wheel
- Forward/reverse for controlling flying sparks



HAZET No.	mm	rpm rpm	∆ <sup>1</sup> ∆ kg	I/min	)))) db (A) Lp A	∭ m/s²	<b>⊚</b> mm			D	EAN-No. 4000896+	
9033N-4	-	19,000	0.8	94	83.8	1.88	330x 10	1	12.91 (1/4")	7.2	210183	
9033N-7	10	12,000	2	113	85	6.5	125 x 22	1	12.91 (¹/₄")	7.2	205547	
9033P-8	10	14,000	1.7	113	89.5	3.65	100 x 0.8 x 9.53	1	12.91 (1/4")	7.2	190515	
9033-10	10	18,000	0.9	114	88	1.8	76 x 2.1 x 10.0	1	12.91 (¹/₄")	7.2	196371	





330 x 10 mm Spare parts




125 x 1 x 22.23 mm



100 x 1 x 9.53 mm



76 x 2.1 x 10 mm





### Grinder

# Micro die grinder • Power: 190 watts

- 3 mm collet chuck



 $\overline{\Phi},\overline{\Phi}$ 

kg

0.2

0.4

Ø mm

5

75

43.7

# Mini die grinder • Power: 224 watts

- 6 mm collet chuck with 3 mm adapter to accommodate both grinding pad dimensions


9032M-36












### 9032M-36 Spare parts

HAZET No.

9032M

Ø 16 mm E C MARKET



HP | Watts



### **Bristle grinder set**

• For gentle yet effective cleaning of surfaces

mm

3

3/6

rpm

60,000

30,000

 $\bullet$  Roloc  $^{\text{TM}}$  quick-change system allows the abrasive media to be changed quickly and easily without needing to use any extra tools






)D

dB(A) Lp A

dB(A) Lp W

THE STATE





17

9033-11/17	50	15000	0.54	79	6.3	0.3	224	10	75
	700			40		THE R		TOWN CO.	100
Œj,		4	5				10.00	0.00	
Haze	•	7		100					



#### Spare parts

HAZET No.	Designation	Design	4	EAN-No. 4000896+	
9033-11-015	Bristle grinding disc, 1/4" UNC Roloc®	Ø 50 mm	1	222841	
9033-11-020/4	Strip wheel set, Ø 50.8 mm Roloc®	Hard variant	4	222834	
9033-11-030/4	Strip wheel set, Ø 50.8 mm Roloc®	Soft variant	4	222728	
9033-11-036/2	Spare bristle grinder set, purple, Ø 50 mm Roloc®	Grain size: 36	2	222872	
9033-11-050/2	Spare bristle grinder set, green, Ø 50 mm Roloc®	Grain size: 50	2	222865	
9033-11-0120/2	Spare bristle grinder set, white, Ø 50 mm Roloc®	Grain size: 120	2	222858	



Ø 50 mm











### Mini air ratchet | Grinder | Sabre saw

### Mini multifunctional air ratchet

- Power: 224 watts
- Manual retightening: 70 Nm


#### **Contents:**

- Sliding ratchet 17 mm
- Socket 1/4", socket 3/8", screwdriver bit socket 6.3 mm
















HAZET No.	max. Nm	rpm rpm	<b>∆</b> <sup>1</sup> ∕ <sub>kg</sub>	Ø mm	I/min	)))) dB(A) Lp A	∭ m/s²				EAN-No. 4000896+	
9023M-1	54	400	0.5	10	84	82.8	3.2	1	12.91 (1/4")	7.2	227112	

#### Spare parts, ratchet socket

	HAZET No.	EAN-No. 4000896+	
1	9023 M-1-020	228225	
2	9023 M-1-021	228232	
3	9023 M-1-B	228249	

### Die grinder, straight design

- Grinding, polishing, burnishing and deburring
- Extremely powerful device (700 watts)



			<b>b</b>						
HAZET No.	mm	rpm	<b>∆</b> <sup>1</sup> ∕ <sub>kg</sub>	I/min	∭∑ dB(A) Lp A	m/s²	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	EAN-No. 4000896+	
9032P-1	6	22,000	0.8	150	87	0.46	1	190508	





Order now!

#### **Accessories**

	HAZET No.	Designation	EAN-No. 4000896+	
1	9000-040	Rotary joint with continuous air flow rate reducer (12.91 mm 1/4")	195350	
2	9030R-01/2	Eraser disc, max. rpm 4,000, Ø 98 mm, thickness: 15 mm	241804	






**NEW!** 

#### Sabre saw

- Increased efficiency with reduction of weight, air consumption, noise generation and vibration
- · Direction of air exhaust adjustable
- Saw stroke: 10 mm
- Strokes/min.: 9500
- Cutting capacity in sheet steel 3 mm, aluminium: 4 mm

HAZET No.	∆ <sup>1</sup> ∆ kg	Ømm	I/min	)))) db (A) Lp A	m/s²	EAN-No. 4000896+	
9034P-2	0.4	10	99	86.7	6.13	218288	





#### Spare parts

HAZET No.	Designation	Design	4	EAN-No. 4000896+
9034P-R/5	Reciprocal saw blades, chamfered teeth	Length: 153 mm	5	218318
9034P-050/5	File set	Length: 153 mm	5	218349
9034P-018/5	Saw blades, 93 mm	18 teeth	5	225958
9034P-024/5	Saw blades, 93 mm	24 teeth	5	225965
9034P-032/5	Saw blades, 93 mm	32 teeth	5	225989

Reciprocal saw blade

### Chisels

# HAZET

#### **Chisel hammer set**

• Including keyless drill chuck





#### Spare parts

HAZET No.	Designation	Ţ.	EAN-No. 4000896+	
9035H-01	Flat chisel	1	214136	
9035H-02	Sheet metal cutting chisel	1	213924	
9035H-03	Pointed chisel	1	214198	
9035H-04	Rivet cutting chisel	1	214143	
9035H-05	Curve cutting chisel	1	214525	



#### **Vibration chisel set**


• Including keyless drill chuck





#### Spare parts and additional vibration chisels

HAZET No.	Designation	*	EAN-No. 4000896 +
9035V-01	Semi-circular vibration chisel	1	214181
9035V-02	Round vibration chisel	1	214174
9035V-03	Vibration chisel	1	214167
9035V-04	Vibration chisel	1	214150
9035V-05	Flat vibration chisel	1	227266
9035V-06	Vibration drift pin 6 mm	1	227259
9035V-08	Vibration drift pin 8 mm	1	227297
9035V-09	Curved vibration chisel	1	227280
9035V-010	Vibration drift pin 10 mm	1	227273



#### Basic unit and keyless drill chuck

# One basic unit – many options!











	HAZET No.	Designation	<b>∆</b> <sup>t</sup> ∕ <sub>kg</sub>	I/min	bar	)))) db (A) Lp A	EAN-No. 4000896+	
1	9035VH	Basic unit with vibration and hammer function, in case incl. keyless drill chuck	2.5	57-594	6.3	92-105	214020	
2	9035VH-01	Keyless drill chuck	0.3	_	_	-	214242	





### Needle scaler Air blow and suction gun

#### Mini needle scaler

- Gentle cleaning of soiled / rusted parts
- 13 needles, Ø 1.3 mm
- 3,000 impacts/min
- · With safety lever
- · Infinite adjustable power
- Extremely handy tool
- · Pin shape for flexible handling
- Free needles allow you to reach difficult to access areas as well
- Coupler plug: nominal size 7.2 (included)




#### 9035M-5

EAN-No. 4000896232284



∆ ∆ kg	I/min	))))) db (A) Lp A	m/s		
0.5	48.1	87.9	6.9	12.91 (1/4")	7.2





#### Spare part

HAZET No.	Designation	Ø	<b>.</b>	EAN-No. 4000896+	
9035M-050	Spare needles for mini needle scaler 9035M-5	1.3	13	233205	



### **Needle scaler**

- · Precisely removing rust and such
- 19 needles, Ø 3 mm
- 3,200 impacts/min
- · Adjustable needle cover
- Pistol shape
- Adjustable needle cover enables maximum utilisation of needles
- Two-piece housing design for easy maintenance
- Coupler plug: nominal size 7.2 (included)





#### 9035-5

EAN-No. 4000896 <b>132355</b>	
	•

∆ <sup>1</sup> ∆ kg	I/min	)))) db (A) Lp A	₩ m/s		
2.6	170	97	8.7	12.91 (1/4")	7.2



#### Spare part

HAZET No.	Designation		<b>.</b>	EAN-No. 4000896+	
9035-050	Spare needles for needle scaler 9035-5	3	19	139385	




### Switchable air blow and suction gun

• For sucking up dirt into the dust collection bag as well as for blowing surfaces clean

· With speedy one-hand switching of the function direction









EAN-No. 4000896198382

Vacuum level mmHg	∆ ∆ kg	I/min	bar	)))) db (A) Lp A	00 Lp A	₩ m/s²		
7.5	0.4	96	6.3-10.34	92	97	0.4	12.91 (1/4")	7.2

#### Spare part

HAZET No.	Designation		EAN-No. 4000896+	
9043N-10-08/2	Fine dust bag for 9043N-10. Particularly suitable for sucking up fine dust	1	222827	



### Pneumatic accessories



# Blind rivet gun • Professional riveting, suitable for

- continuous operation with rivets of up to 6.4 mm made of steel, stainless steel, aluminium and copper
- Possible rivet sizes: 3.0 3.2 -4.0 - 4.8 - 5.0 - 6.0 and 6.4 mm
- 5 nose pieces

 $\overline{\Delta}, \overline{\Delta}$ 

- Flexible connecting nipple
- Total stroke: 15.8 mm
- High tractive power: 14700 N
- · Particularly low noise level
- Includes maintenance set for oil control (oil-supported pressure build-up)

/ mm

296.6



#### Grease gun

- · Continuous pumping of grease
- Gun-filling with grease cartridge, loose grease or via dispenser
- Compaction: 40:1
- 360° adjustable handle

230

· Filling capacity: approx. 400 ml



### Mini grease gun

- · Creates pressure up to 1,000 PSI/69 bar
- Suitable for filling with loose grease
- Incl. lubricating nipple in 50° and 90° designs



12.91 (1/4")

### **High performance lubricant**

· Optimal for quickly and cleanly filling the HAZET mini grease gun 2162M



9300N-60

HAZET No.	Designation	EAN-No. 4000896+	
9037N-2	Blind rivet gun	205578	
9042N-1	Grease gun	176472	
2162M	Mini grease gun, filling capacity: 80 g, length: 145 mm, weight: 0.27 g	185634	
9300N-60	High performance lubricant, 60 ml	203406	
9070N-1	Mini oiler, 28 ml	206407	
9400-100	Special pneumatic tool oil, 100 ml	191390	
9400-1000	Special pneumatic tool oil, 1000 ml	191406	

#### Mini oiler

mm Nylon hose

230

- · Supports longevity and permanent functionality
- Reduces wear of the air motor

mm Metal tube

172

12.91 (1/4")

· Working pressure: 6 bar



12,91(4)

9070N-1

### **Special pneumatic** tool oil

Made in Germany

9400-100 / 9400-1000

#### Hose reel

- Suitable for compressed air or water
- · Black hybrid polymer hose
- · Automatic guidance winds the hose neatly
- 9040N-13: Meets all relevant requirements defined in European Machinery Directive 2006/42/EC



HAZET No.	°C	Outside thread	Hose inside Ø mm	<b>O</b> bar	∆ <sup>1</sup> ∆ kg	EAN-No. 4000896+	
9040N-10	-40°/+60°	16.41 mm <sup>3</sup> /8"	10	20	6.45	206445	
9040N-13	-40°/+80°	20.96 mm ½"	13	20	9.5	214648	

#### Cable reel

- · Including line circuit breaker
- · Only suitable for indoor use

230V AC Cable: H07RN-F 3 x 2.5 mm<sup>2</sup>



H <u>AZET</u> No.	°C	watts	watts	∆ <sup>t</sup> ∆ kg	EAN-No. 4000896+	
9040D-2.5	- 20/+ 45°	1600	3200	9.2	214631	



### Pneumatic adapters Pneumatic accessories

#### 9000-040





# **Rotary joint with continuous**

• 360° rotation joint in 2 axles

air flow rate reducer

- · Air flow regulation by means of setting wheel
- Release of the rotating function through compressed air supply, rigid in unpressurised condition

9000-041





### **Rotary joint**

- 360° rotation joint in 2 axles
- . Maximum pressure: 16 bar



HAZET No.	Outside thread	Inside thread	Δ <sup>1</sup> Δ kg	EAN-No. 4000896+	
9000-040	12.91 mm <sup>1</sup> / <sub>4</sub> "	12.91 mm <sup>1</sup> / <sub>4</sub> "	0.09	195350	
9000-041	12.91 mm <sup>1</sup> / <sub>4</sub> "	12.91 mm <sup>1</sup> / <sub>4</sub> "	0.07	204441	

#### Safety couplings

- Safe disconnection of the connection (unwanted disconnection is excluded)
- No risk of injury from hose impact
- Safety coupling depressurizes the connection before decoupling
- One-hand operation
- Little effort during coupling and decoupling
- · Omission of loud popping during coupling process
- Easy operation, even with gloves
- 9000-050 · 051 · 060 · 061 · 070 brass, nickel-plated







9000-060



9000-070





#### Compressed air reducer

- Reduction of working pressure to protect high-quality pneumatic equipment
- Inline pressure regulator for integration in the compressed air line or direct connection to motorised pneumatic equipment
- Including:
  - Adapter from outside thread (1/4") to outside thread (1/4") for connecting to the device
  - Air connection nipple 7.2 Type 1 for connection to compressed air coupling
- Max. inlet pressure: 10 bar
- Outlet pressure: 6.3 bar

HAZET	Outside	Inside	Д Д	EAN-No.	
No.	thread	thread	kg	4000896+	
9000-080	12.91 mm <sup>1</sup> / <sub>4</sub> "	12.91 mm <sup>1</sup> / <sub>4</sub> "	0.1	214709	



#### **Spiral hose** High flexible polyurethane hose

- Connecting pieces with 360° rotary joints

HAZET No.	[ m	Burst pressure according to DIN	Hose inside Ø mm	bar			EAN-No. 4000896+	
9040-7	7.62	55.1 bar/800 PSI	6.35	10	12.91 (1/4")	7.2	153404	
9040S-10**	7.62	60 bar	10	10	12.91 (¹/₄")	7.2	212361	



\*\* Recommended by HAZET for commercial application  $\varnothing$  10 mm

### Cleaning equipment



### Air blow guns

9040P-1

9040P-4

- With bent pipe Ø 8 mm, 100 mm
- Application field: -10°C to +80°C





- With bent pipe Ø 8 mm, 100 mm
- · Extreme reduction of noise
- Non-blocking Max. 12 bar



9040P-2

- With bent pipe Ø 8 mm, 100 mm
- 100% increase in air outlet quantity thanks to Venturi



- With wide flat nozzle for cleaning surfaces
- Low noise


9040P-5



• 2-way air blow gun

- Choice of air supply at tool head or handle
- · Pressure regulator and replaceable nozzles
- Max. 10 bar
- · With 112 mm nozzle





### Venturi nozzle

- 100% increase in air outlet quantity thanks to Venturi effect
- · For blowing out machines, cargo spaces and buildings in industry, agriculture and trade
- Optional Venturi nozzle for 9040-4 and 9040LG-3/2



### Lateral nozzle

- · Nozzle allows lateral blowing out
- Cleaning cooling fins and other hard-to-reach areas
- · Optional lateral nozzle for 9040-4 and 9040LG-3/2



# Air blow gun, long

### Car body gun for underbody protection and cavity sealing

- · Including metal suction pipe
- Suitable for aqueous and oily liquids
- · Including nozzle and cavity tube
- Application field: -10°C to +80°C
- Air requirement with cavity tube: 180 I/min at 8 bar



HAZET No.	∆ <sup>1</sup> ∆ kg	I/min	bar			EAN-No. 4000896+	
9042P-4	0.3	255	6	12.91 (1/4")	7.2	209613	

### Soda spray gun

• Mineral spray gun for damage-free cleaning and removal of paint

1.085

- No heating / deformation of sheets during blasting
- Removes paint from wooden objects without any damage
- Removes paint from glass surfaces and window frames without causing damage to glass and seals
- For blasting with NaHCO3 (sodium bicarbonate)
- Including 1 kg of soda blast-cleaning agent!





Incl. 1x

9040LG-3/2 EAN-No. 4000896206339





HAZET No.	<b>∆</b> ' <b>∆</b> kg	I/min	bar	)))) db (A) Lp A	00 (W) Lp A	₩ m/s²	EAN-No. 4000896+	
9045P-1	0.5	280	6 – 12	88.3	89.4	1.44	209590	
9045P-5S	Soda bla	Soda blast-cleaning agent, 5 kg for soda spray gun					210404	



### Cleaning equipment | Heat gun set

### Wash-gun set


- Effective, powerful and solvent-free cleaning of e.g. cooling systems
- · Cleaning for cooling systems without the use of aggressive chemicals or
- · Swivel joint at the water connection, helps to avoid "hose spaghetti"
- · Continuous independent regulation of water and compressed air supply
- · Washing and system cleaning nozzle included
- . No splashback even when cleaning with combined water/compressed air jet at
- . Damage-free cleaning thanks to water / air operation
- · Quick, easy and gentle cleaning
- · High-quality materials
- Water connection 1/2" nipple for water coupling (Gardena system compatible) or 3/4" GHT thread

#### Contents:

- Water connection options 1/2" (13 mm) or 3/4" hose thread
- Graduated system cleaner nozzle
- Jet washing nozzle







bar max.	°C	Ø mm air	Ø mm water
6-10	-10 / +40	10	13







### Heat gun set

- Power: 2.300 watts
- . 5 storage functions (air stage / temperature)
- · Optimised flow guidance
- Digital temperature control (integrated temperature probe)
- Configurable Power Safety Function (eco-mode)
- Eco 1 movement-triggered eco function
- Eco 2  $position\mbox{-triggered}$  eco function (saves up to 40 % energy and reduces the noise level up to 50 %)
- · Ceramic heating element
- Temperature control concept (Close Loop)
- Soft touch handle area
- Best ergonomics, even distribution of weight
- Standby position (standby key): When the hash key is pressed, the device swivels to the standby function
- · Long life engine class: 1 kh
- Temperature range (electronically controlled and continuously adjustable): 80-650°C
- Air flow range (I/min at 20°C: 200-550 I/min), electronically controlled and continuously adjustable
- Complete unit tested for 1,000 h


#### Contents (set):

- Basic unit - 4 x nozzles
- (spoon reflector nozzle angled at 90°, solder reflector nozzle, pipe nozzle wide slot nozzle angled at 15°)
- Pressure roller 30 mm wide
- L-Boxx 136










	HAZET No.	Designation	4	EAN-No. 4000896+	
1	1990N-010	Heat gun, basic unit	1	241088	
2	1990N-020/5	Accessories set for heat gun: spoon reflector nozzle 90°, solder reflector nozzle, wide slot nozzle 15°, pipe nozzle, pressure roller	5	241101	
3	1990N-01	Protective ring for heat gun nozzle pipe (protects against burns and ensures safe storage)	1	241118	
4	190L-136	L-Boxx 136	1	237616	





### **Cordless right-angle grinder** 18 V, 5.0 Ah

- High efficiency thanks to brushless motor
- . Device stops if the speed drops sharply due to canting
- · With function against unintentional motor start when changing the battery
- Mesh fabric protects motor from dirt
- . Motor stop 2 seconds after switch-off
- Constant speed even during difficult work

44

2.28

<u> 4'4</u>

kg Without rechargeab

1.53

- · Soft startup for greater comfort
- With safety lever
- · Quick adjustment of protection cover without tools
- Spindle thread: M14

(rpm)

rpm

8,000

· Delivery in plastic case

**)** 

db(A)LpA

89







- -9233-011/10, rough grinding wheel set, 10 pieces
- 9233-010/25, cut-off wheel set, 25 pieces

HAZET No.	Designation	4	EAN-No. 4000896+	
9233-010	nit cordless right-angle grinder (without rechargeable battery, without charger) set: 1 cordless right-angle grinder, 1 quick charger, 1 Li-ion rechargeable battery 18 V, 5.0 Ah		218943	
9233-7	piece set: 1 cordless right-angle grinder, 1 quick charger, 1 Li-ion rechargeable battery 18 V, 5.0 Ah		218325	
9233-7/4			218950	





### **Cordless drilling machine** 18 V, 2.0 Ah

- Tool-free metal quick-clamping drill chuck 1–13 mm
- · Incl. quick charger
- Selectable torque settings 15 + 1 drilling
- Delivery in cloth bag





max.	rpm	rpm	))D
Nm	rpm	rpm	db(A) Lp A
60	1 0-560	② 0-1900	68





### **Cordless impact wrench** 18 V, 2.0 Ah

### Max. loosening torque: 260 Nm

- Extremely handy tool
- Amperage without load: 5 A
- · Delivery in cloth bag
- Impacts per minute: 0 3300





max. Nm	max. Nm	rpm rpm	)))) db (A) Lp A	₩ith rechargeable battery	↓↓ kg Without rechargeable battery
200	260	2,700	100	1.45	1.06



### Mini cordless impact wrench 18 V, 2.0 Ah

### Max. loosening torque: 270 Nm

- Extremely handy and short tool
- Three selectable performance levels for torque screw tightening

Level 1: approx. 80 Nm at 700 rpm Level 2: approx. 150 Nm at 1,600 rpm Level 3: approx. 220 Nm at 2,500 rpm

- Impacts per minute: 0-1,200 / 0-2,000 / 0-3,200
- Amperage without load: 4.5 A
- · High efficiency thanks to brushless motor
- Brushless DC motor (BLDC):
  - Longer service life, less wear, no need to change the carbon brushes
- High efficiency and hence less battery consumption
- More compact motor enables smaller dimensions
- · Delivery in cloth bag





max. Nm	max. Nm	rpm	)))) db (A) Lp A	∆ <sup>1</sup> ∆ kg With rechargeable battery	₩ithout rechargeable battery
220	270	2,500	99.6	1.34	0.95

HAZET No.		Designation	4	EAN-No. 4000896+	
9230-010	-	Basic unit cordless drilling machine (without rechargeable battery, without charger)	1	218974	
9230-2	-	3-piece set: 1 cordless drilling machine, 1 quick charger, 1 Li-ion rechargeable battery 18 V, 2.0 Ah	3	218370	
9230-2/4	-	4-piece set: 1 cordless drilling machine, 1 quick charger, 2 Li-ion rechargeable batteries 18 V, 2.0 Ah	4	218967	
9212SPC-010	125 1/2	Basic unit cordless impact wrench 18 V (without battery, without charger)	1	214273	
9212SPC-1	125 1/2	3-piece set: 1 basic unit, 1 charger, 1 Li-ion rechargeable battery 2.0 Ah	3	212439	
9212SPC-1/4	125 1/2	4-piece set: 1 basic unit, 1 charger, 2 Li-ion rechargeable batteries 2.0 Ah	4	214259	
9212M-010	125 1/2	Basic unit mini cordless impact wrench 18 V (without battery, without charger)	1	214280	
9212M-1	125 1/2	3-piece set: 1 basic unit, 1 charger, 1 Li-ion rechargeable battery 2.0 Ah	3	212446	
9212M-1/4	125 1/2	4-piece set: 1 basic unit, 1 charger, 2 Li-ion rechargeable batteries 2.0 Ah	4	214266	

9212-1000/3

1/2"





# Cordless impact wrench 18 V, 5.0 Ah Cordless impact wrench 18 V, 5.0 Ah

Max. loosening torque: 1,400 Nm

• Three selectable performance levels for torque screw tightening:

Level 1: approx. 180 Nm at 0 – 400 rpm Level 2: approx. 400 Nm at 0 – 800 rpm Level 3: approx. 1,000 Nm at 0 – 1,800 rpm

- $\bullet$  Impacts per minute: 0 800 / 0 1,600 / 0 2200
- Illumination of the work area
- before the output begins to move
- Suitable for continuous operation
- Charging time at 5 Ah battery: approx. 80 min
- Loosening torque (max) determined with screw size M: 24
- High efficiency thanks to brushless motor
- Brushless DC motor (BLDC):
  - Longer service life, less wear, no need to change the carbon brushes
- $-\mbox{ High efficiency}$  and hence less battery consumption
- $\ \mbox{More compact motor enables smaller dimensions}$
- In plastic case

Nm

1,000

Nm

1,400

rpm

1,800

# smaller dimensionsDelivery in L-Boxx 136



More compact motor enables

Max. loosening torque: 700 Nm

• 18 V, 5.0 Ah, Li-ion rechargeable battery

• Impacts per minute: 0 - 1,200 / 0 - 2,500 / 0 - 3,400

Longer service life, less wear, no need to change the

- High efficiency and hence less battery consumption

• Charging time at 5 Ah battery: approx. 80 min

• Three selectable performance levels

for torque screw tightening Level 1: approx. 80 Nm at 600 rpm Level 2: approx. 300 Nm at 1,400 rpm Level 3: approx. 500 Nm at 2,000 rpm

Amperage without load: 5.5 A

with screw size M: 16

carbon brushes

• Brushless DC motor (BLDC):

Loosening torque (max) determined

High efficiency thanks to brushless motor





**)** 

db(A) Lp A

battery



battery

max. Nm	max. Nm	rpm	))))) db (A) Lp A	kg With rechargeable battery	& ↓ ↓ kg Without rechargeable battery
1.000	1.400	1.800	101	3.70	3.04

HAZET No.		Designation	4	EAN-No. 4000896+	
9212-010	125 1/2	Basic unit cordless impact wrench 18 V (without battery, without charger)	1	221790	
9212-3LB/3	125 1/2	3-piece set: cordless impact wrench 18 V, 1 charger, 1 Li-ion rechargeable battery 5.0 Ah, in L-Boxx	3	244164	
9212-3LB/4	125 1/2	4-piece set: cordless impact wrench 18 V, 1 charger, 2 Li-ion rechargeable batteries 5.0 Ah, in L-Boxx	4	244171	

9212-1000	125 1/2	Basic unit cordless impact wrench 18 V (without battery, without charger)	1	222711	
9212-1000/3	125 1/2	3-piece set: 1 basic unit, 1 charger, 1 Li-ion rechargeable battery 5.0 Ah	3	222674	
9212-1000/4	125 1/2	4-piece set: 1 basic unit, 1 charger, 2 Li-ion rechargeable batteries 5.0 Ah	4	222681	

9213-1000	20 3/4"	Basic unit cordless impact wrench 18 V (without battery, without charger)	1	222698	
9213-1000/3	20 3⁄4″	3-piece set: 1 basic unit, 1 charger, 1 Li-ion rechargeable battery 5.0 Ah	3	222704	
9213-1000/4	20 3⁄4″	4-piece set: 1 basic unit, 1 charger, 2 Li-ion rechargeable batteries 5.0 Ah	4	222797	



9213-1000/3

3/4"

20 3/4"



### Cordless reciprocating saw set 18 V, 5.0 Ah

- Support frame, adjustable in height, suitable for double-walled sheet steel
- Work independently
- High efficiency thanks to brushless motor
- . Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- Tool-free saw blade quick-change system
- · Quick bracket adjustment
- Composite housing

Contents:

Brushless DC motor (BLDC):

- Cordless reciprocating saws

- Longer service life, less wear, no need to change the carbon brushes
- High efficiency and hence less battery consumption
- More compact motor enables smaller dimensions

"The machine is extremely compact – just the right thing for difficult places, e.g. on the roof timbers!"

Níls



























∆ ∆ kg With rechargeable battery	∆¹∆ kg Without recharge- able battery	Strokes/min.	Saw stroke mm	)))) db (A) Lp A	m/s²
2.95	2.26	0 – 3,100	28.5	86.13	32.18

In the new HAZET L-Boxx 190L-136

HAZET No.	Designation	4	EAN-No. 4000896+	
9234-010	Cordless reciprocating saw basic unit (without rechargeable battery, charger, L-Boxx and insert)	1	234707	
9234-1	3-piece set: 1 cordless reciprocating saw, 1 quick charger, 1 Li-ion rechargeable battery 18 V, 5.0 Ah	3	234714	
9234-1/4	4-piece set: 1 cordless reciprocating saw, 1 quick charger, 2 Li-ion rechargeable batteries 18 V, 5.0 Ah	4	234721	



#### Made in Germany

#### Spare parts









		HAZET No.	Designation	L x W x H mm	Length of serration mm	4	EAN-No. 4000896+	
(	1)	9234M-150/5	Flexible reciprocating saw blades for steel and non-ferrous metals from 2 – 8 mm	150 x 19 x 0.9	130	5	239382	
(	2	9234P-150/5	Flexible reciprocating saw blades for wood with nails and faster sawing progress in metal 2 – 10 mm.  New serration for long service life.	150 x 19 x 0.9	130	5	239405	
(	3	9234P-225/5	Flexible reciprocating saw blades for wood with nails and faster sawing progress in metal 2 – 10 mm.  New serration for long service life.	225 x 19 x 0.9	205	5	239412	
(	4	9234X-150/5	Flexible reciprocating saw blades for steel and stainless steel (lnox) from 1.5 – 4 mm	150 x 19 x 0.9	130	5	239597	
	5	9234W-225/5	Rigid reciprocating saw blades for all wood, plastics as well as plasterboard (6 - 100 mm)	225 x 19 x 1.27	205	5	239429	

Spare part		<b>6</b>	Him	INT INT					1 5
⑥ 9034P-R/5	Reciprocal saw blades, chamfered teeth				152 x 19 x 1	132	5	218318	

### Thermal camera



### Thermal camera

- Application in building diagnostics, electrical installation, sanitary, air-conditioning and heating technology
   Inspection of the engine compartment, the brake system and the cooling and heating system on passenger cars
   Colour palettes: White Hot, Black Hot, Rainbow, Ironbow

- Image sensor: Vanadium oxide uncooled focal plane arrays (FPA)
- Storage medium: exchangeable SD card 8 GB, up to 150,000
- · Automatic hot, cold and central point measurement
- · Laser pointer





Unit Central point Status temperature symbols Hot point Cold point Central point Min./max. temperature





Emissivity







Including hand strap



Including SD card



Delivery in high-quality packaging



Screen size	Refresh rate Screen resoluti Pixel		Thermal (or IR) resolution Pixel	Thermal sensitivity (NETD)	Field of vision
2.4" LCD screen	25 Hz	320 x 240	160 x 120	< 40 mK (0.04° C)	37.2° x 50°

Temperature measuring range	Measuring accuracy Max. (±2°C, ±2%)	Protection rating IP	Battery life	Dimensions mm (H x W x D)		<b>∆</b> <sup>1</sup> ∕ <sub>kg</sub>
-20 °C to 550 °C (-4 °F to 1,022 °F)	Ambient temperatures 15 °C – 35°C / Object temperatures over 0 °C	54	up to 8 h	196 x 117 x 59	Lithium-lon rechargeable battery	0.35




### Video borescope | Overview


### Video borescope

- Display resolution: 800 x 480 pixels
- 8-stage brightness setting (5 + 3 boost)
- · Zoom: 3-step
- . Display of battery capacity
- · Timestamp can be shown
- · Record photos and videos
- . Mirroring and negative display of the camera image possible
- Designation of photos possible
- Data transfer: USB-C
- . Charger: USB charging adapter DC-5V / 3 A
- High-tech borescope in compact design
- Detailed illustration
- · Easy to read, even in sunlight
- · Easy to handle
- 5 inch touch display readable in sunlight

"Great product for small localising jobs! You can reach the smallest corners and don't have to make big holes!"











# Newest generation!

- High-tech borescope in compact design
- Detailed illustration
- Easy to read even in sunlight
- Easy to handle
- 5 inch touch display readable in sunlight
- Not compatible with previous models



HDMI port for video output, USB-C for charging, Micro SD

Swivelling magnetic base, 180° adjustable

Touch display







Comparison: Display resolution of current probe (left) with new probe (right)

Display resolution: 320 x 240 pixels Display resolution: 800 x 480 pixels







Operational readiness (h)	IP protection rating (basic unit)	IP protection rating (with probe)	Charging time (h)	Battery charger	<b>(</b>
4	IP 54	IP 67	3.5	USB charging adapter DC-5V / 3 A	Li-ion battery

PI

### Video borescope sets



5

### **Borescope set with semi-flexible probe** Ø 5.5 mm

- Ø 5.5 mm with micro lens
- Semi-flexible probe with 1 m probe cable
- Front camera: 0°
- Image resolution 1,024 x 768 Pixel
- Focus range: 10 to 60 mm
- Focus angle: 56°
- 4-way LED luminous source







#### 4812-21/5S


EAN-No. 4000896238811

#### Contents:

- Basic unit 4812-21
- Probe 4812-21S
- USB-C to USB-A cable
- Aluminium case



### **Borescope set with swivelling probe** Ø 4.5 mm



- Compatible with basic unit 4812-21
- Bending radius only approx. 38 mm (-30 % compared to conventional designs)
- · Front camera
- Image resolution 1,024 x 768 Pixel
- . Focus range: 10 to 100 mm
- Focus angle: 90°
- $\bullet \varnothing$  4.5 mm with micro lens
- 1 m probe cable
- 5-way LED luminous source



4812-21/5AF

EAN-No. 4000896239283

#### Contents:


- Basic unit 4812-21
- Probe 4812-21AF
- USB-C to USB-A cable
- L-Boxx 136











### Probes for video borescope

HAZET No.	Designation	EAN-No. 4000896+	
4812-21S	Semi-flexible probe $\varnothing$ 5.5 mm, front camera: 0°	237623	
4812-21AF	Swivelling probe 180° Ø 4.5 mm, front camera	237630	

### Video borescope with swivelling probe

- Up to 180° swivel enables e.g. a real reverse view onto valves in the cylinder
- Camera head only 11 mm long (-50 % compared to conventional designs)
- Bending radius only approx. 38 mm (-30 % compared to conventional designs)
- · Light boost and integrated reflection reduction
- $\bullet$  Micro-lens:  $\varnothing$  4.5 mm Front view with a resolution of 640 x 480 pixels
- · Casing made from steel mesh
- Image resolution: 640 x 480 pixels
- Display resolution: 320 x 240 pixels

### • Contents:

- 1 m probe cable with  $\varnothing$  4.5 mm micro-lens and LED luminous source
- Operating panel
- SD card with 4 GB storage capacity
- 4 x AA batteries



EAN-No. 4000896219131





### Video borescope with Ø 4.9 mm switch probe

- Image resolution: 640 x 480 pixels
- Display resolution: 320 x 240 pixels

#### Contents:

- 1 m probe cable with  $\varnothing$  4.9 mm micro lens and LED luminous sources
- Hook including magnet
- SD card with 4 GB storage capacity
- 4 x AA batteries

#### 4812-10/4S

EAN-No. 4000896181742







#### Probes for video borescope

HAZET No.	Designation	EAN-No. 4000896+	
4812-16	Ø 4.9 mm / 0° + 90°	181841	
4812N-1 S	Ø 3.9 mm / 90°	187102	
4812N-1 F	Ø 3.9 mm / 0°	187096	
4812N-5.5	Ø 5.5 mm / 0°	187065	
4812N-2 AF	Ø 4.5 mm swivelling probe	218868	



4812 N-2 AF



### Wireless charging LED lights





# LED light set, wireless charging

- Efficient and comfortable charging function due to optimised self-positioning of the lamp on the pad
- Wirelessly mobile and versatile, especially in extremely tight spaces

#### **Contents:**

- 1979W-82 LED Pocket Light
- 1979W-92 LED Slim Light
- 1979WP-2 Charging pad for 2 lamps
- USB-C cable, 100 cm
- Power supply unit 5 V, 2 A

1979W1/3

EAN-No. 4000896**241408** 



# Wireless charging LED lights







- Contents:

   2 x 1979W-11 Pen Light

   1979WP-2 Charging pad for 2 lamps

   Incl. 100 cm USB-C cable and 2 A 5V mains plugs





EAN-No. 4000896235247





### **LED** inspection lamp set, wireless charging

- Contents:

   1979W-11 Pen light

   1979W-82 Pocket Light

   1979WP-2 Charging pad for 2 lamps

   Incl. 100 cm USB-C cable and 2 A 5V mains plugs



14



EAN-No. 4000896235261











# LED lights

### Wireless charging







Charging pad
• Including 100 cm USB-C cable (with USB adapter)



1979WP-1 EAN-No. 4000896227952

For 1 light



1979WP-2 EAN-No. 4000896**227945** 

For 2 lights

HAZET No.	Operating time (h) Main light	Operating time (h) Top light	Luminous flux Lumen	Protection rating IP	Protection rating	Charging time (h)		[ mm	EAN-No. 4000896+	ı
1979W-82	2 – 10	5	30 – 300	IP 65	IK 09	1.5	3.7 V 1,200 mAh, Li-ion rechargeable battery pack	133	227228	
1979W-11	2.5 – 10	4	20 – 200	IP 65	IK 09	2.5	3.7 V 1,050 mAh, Li-ion rechargeable battery pack	180	235230	1
1979W-85	3 – 20	4.5	60 - 600	IP 65	IK 09	3.5	3.7 V, 2,600 mAh	255	241484	
1979W-92	3 – 14	11	110 - 1 100	IP 65	IK 08	5.5	3 6 V 4 500 mAh lithium-ion rechargeable battery	367	241422	

### With charging cable

Delivery incl. 100 cm USB-C charging cable (without USB power box)

1979W-11



1979W-82

















### With batteries

• 1.5 V Micro / AAA / (L)R03





1979N-72

HAZET No.	Operating time (h) Main light	Operating time (h) Top light	Luminous flux Lumen	Protection rating IP	Protection rating	Charging time (h)			EAN-No. 4000896+	
1979N-82	2 – 10	5	30 – 300	IP65	IK09	1.5	3.7 V 1,200 mAh, Li-ion rechargeable battery pack	133	227211	
1979-11	2.5 – 20	4	20 – 200	IP65	IK09	2	3.7 V 1,050 mAh, Li-ion rechargeable battery pack	180	235254	
1979N-85	3 – 20	4.5	60 - 600	IP65	IK09	3	3.7 V 2,600 mAh, Li-ion rechargeable battery pack	255	241491	
1979N-92	3 – 14	11	110 - 1,100	IP65	IK08	4.5	3.7 V 4500 mAh, Li-ion rechargeable battery pack	367	241415	
1979N-71	4	_	130	IP45	IK07	-	2 x AAA-1.5 V batteries (incl.)	139	208470	
1979N-72	4	_	200	IP45	IK07	-	3 x AAA-1.5 V batteries (incl.)	135	208487	

### Workshop tools



### **Pressure sprayer**

- Capped pumping mechanism increases chemical resistance
- Viton® gaskets
- Integrated safety valve (2.5 bar)
- Particularly suitable for disinfection

Spraying with chemical and corrosive substances!









### Pressure sprayer, foam

- Recommended for foaming disinfectants, as well as neutral, acidic and alkaline cleaners
- Integrated safety valve (2.5 bar)

Creation of tight, permanent and visible foam!



199-3

EAN-No. 4000896207237





**Genuine leather** working gloves

HAZET No.

1987N-3

1987N-4

1987-5L

1987-6

1987-5XL

1987-5XXL



Working gloves with micro-foam coating



Mechanic's gloves



Mechanic's gloves



1987N-4 1987-5

Material	Size	EAN-No. 4000896+	
High-quality mix of materials from genuine leather and modern microfibre textiles	One size	222650	
60% cotton, 40% polyester	One size	203840	
48% polyamide/nylon, 25% polyacrylic, 25% polyester, 2% polyurethane	L	181735	
48% polyamide/nylon, 25% polyacrylic, 25% polyester, 2% polyurethane	XL	181759	
48% polyamide/nylon, 25% polyacrylic, 25% polyester, 2% polyurethane	XXL	181766	
The selection of the continuous fields of the continuous	0	000040	



### Mechanic's creeper

• Especially deep for maximum freedom of movement under the vehicle

The palm has a high-quality nitrile rubber coating

• Rigid one-piece construction made of high strength plastic, black





Loading capacity kg	<b>∆</b> ∆ kg
130	5.8
	capacity kg

195-2

EAN-No. 4000896125982

AN-110. 4000030 1 20302	

### **Pneumatic chair**

- Height-adjustable 380 510 mm
  2 tool compartments
- Tilt-resistant
- · Easy to clean



Dimensions H x L x D mm	Loading capacity kg	<b>∆</b> <sup>1</sup> ∕ <sub>kg</sub>
380-510 adjustable in height	150	5.8



195-4

EAN-No. 4000896148707



YA




### Workshop tools

#### **Brush oiler**

- Application of an even lubricating film to workpieces, surfaces and chains ensures tool-friendly distribution of coolants and lubricants while drilling
- · Industrial oiler with single pump
- Due to the 20 bar pumping unit, the oiler is also able to pump heavier oils efficiently. This is especially advantageous when oiling chains and slide rails.
- 300 ml container made of PEHD
- · Replaceable brush, 20 mm diameter
- · For higher viscosities
- Brass lance
- · Suspension lug
- Semi-transparent container for better visibility of the filling level





#### 2160-1





#### Spare parts

HAZET No.			EAN-No. 4000896+	
2160-1-01/2	Replacement brush set for brush oiler	2	238866	
2160-1-02	Pump mechanism with seals	1	238873	

### **Multifunctional drain pans**


• For oil change / oil filter replacement and for cleaning of parts





HAZET







#### Dashboard protection with handle

• Angled (270 x 200 mm, 450 x 300 mm) and straight (270 x 200 mm, 450 x 300 mm)



Made in Germany

195-1

**Kneeling mat** 

· Easy-to-clean surface

195-5

Mechanic's mat

· Easy-to-clean surface



### 9070-10 Magnetic holder

. Loading capacity: 10 kg

197-3

#### Magnetic cup


- · With magnet for fixing
- Ø 150 mm



### 1977-2/4

### **Telescopic inspection** mirror set

• Double hinge with tension spring



HAZ No	T Function	EAN-No. 4000896+			
4852/4	For protection against damage to the dashboard, interior lining and vehicle headlining when removing windows				
195-1	Kneeling mat 30 x 450 x 210 mm (HxWxD)				
195-5	Mechanic's mat 30 x 975 x 385 mm (HxWxD), not shown				
9070-1	With two strong magnets to hold: 1 impact wrench, 4 sockets and 1 torque wrench				
197-3	Holds small parts such as screws etc.				
1977-2	Telescopic rod, extension length: 300 - 740 mm, round mirror: Ø 30 / 50 mm, rectangular mirror: 65 x 43 mm	150144			



### Wheels / tyres

### Wheel hub grinder

- Prevents incorrect wheel bolt tightening torque caused by corrosion
- Quick and easy removal of rust and dirt from contact surfaces of wheel hubs and brake discs with wheel bolt support
- Wear-resistant: approx. 100 vehicles per wheel
- . Open-pored abrasive material and cup-formed grinding wheel reduce the formation of dust to a
- · No formation of sparks








Before





Spare grinding wheels: 4960R-0160/3

#### Contents:

- Base component
- 3x grinding wheels Ø 160 mm







O s 11 mm



 $\bullet$  With  ${\ensuremath{\,\boxtimes\,}} \ensuremath{\,^{1\!\!\!/}}$  inside square collet for attachment e.g. to pneumatic, cordless and corded impact wrenches

Spare grinding wheels: 4960V-0160/3

#### **Contents:**

- Base component
- Grinding wheel  $\varnothing$  160 mm



4960V-160/2









HAZET No.	Inside mm	rpm	Passenger car wheel hub mm	EAN-No. 4000896+	
4960R-160/4	75	500	160	218820	
4960V-160/2	75	500	160	218394	
4960F-160/2	50	500	160	218387	

### Rim flange cleaner

- For optimum cleaning of the contact surface on the rim inside
- 11 mm outside hexagon with 3 contact surfaces for attachment e.g. to pneumatic, cordless and corded drilling machines
- · With centre hole guidance and integrated sander for cleaning the wheel centring
- For wheel centring diameter: min. 51 mm
- Spare grinding wheels: 4960F-0160/3

### **Contents:**

- Base component
- Grinding wheel  $\varnothing$  160 mm

4960F-160/2





#### Spare parts

- Pail o Pail o							
H <u>AZET</u> No. Designation		Ø	4	EAN-No. 4000896+			
496R-0160/3				218790			
4960V-0160/3	With hook and loop fastener	160	3	218813			
4960F-0160/3				218806			



















### 1/2" impact socket (6-point), 85 mm long

• With plastic insert to protect the surface of the wheel bolts







### Sets





Made in Germany

HAZET No.	S mm	[ mm	4	EAN-No. 4000896+	
903SLg-17/3	17 (3x)	85	3	191697	
903SLg-19/3	19 (3x)	85	3	191734	
903SPC/3	17 · 19 · 21	85	3	128754	



### 1/2" special profile, 86 mm long

- Especially for removing wheels and installing light-alloy rims for hybrid wheel bolts in all new MERCEDES-BENZ vehicles
- For e.g. MERCEDES-BENZ C Class type 204, 204X, E Class type 211, 212, 207; SLK type 172;M Class type 164, 166; S Class type 221, 222, CL Class type 216




### Wheels / tyres

### 1/2" socket set FORD wheel bolt 18 x 20 mm

- Releasing tool can be used on both sides, among others for Ford models B-Max, C-Max, EcoSport, Fiesta, Focus, GrandC-Max, KA, Kuga, Mondeo, Puma, Ranger, Tourneo, Transit
- Problem: if the chrome cover is damaged or missing, the wheel nut can no longer be operated with the normal 19 mm socket

### **Contents:**

- 900SLg-18x20 socket
- 917S-3 extension







Made in Germany 900SLG-18x20/2

EAN-No. 4000896242023



s 18 mm For use in the absence of chrome cover



s 20 mm

For use with damaged /

### 1/2" socket FORD wheel bolt 18 x 20 mm

- For impact operation
- · Surface: phosphatized, oiled
- Length: 50 mm



### 1/2" extension

- With locking ball
- For impact operation
- Surface: phosphatized, oiled



125 1/2

Made in Germany 917S-3

EAN-No. 4000896241927

# **Tyre inflators**







HAZET No.	bar	Hose length mm	Manometer measuring range bar	Graduation mm	Manometer mm	<b>∆</b> <sup>1</sup> <b>∆</b> <sub>kg</sub>	EAN-No. 4000896+	
9041-1	8	400	0 – 12	0.1	63	0.4	147076	
9041D-1	12	400	0 – 12	0.01	63	0.4	212378	
9041G-1	10	1000	0 – 10	0.1	80	0.6	212385	

### Oil Service

### 1/2" oil filter wrench

- · Operating oil filters and oil filter housings with outer-Ø 72 mm and 14-point especially for FORD 1.0I / 1.1I and 2.01 EcoBoost engines
- · Positive mounting of the oil filter and oil filter housing
- Required torque-controlled screw tightening is possible
- Outside diameter: 103 mm
- FORD models: B-Max, C-Max, EcoSport, Fiesta, Fiesta Active, Focus, Grand C-Max, Grand Tourneo, Connect, Mondeo, S-Max, Galaxy, Tourneo Connect, Tourneo Courier, Transit Connect, Transit Courier









#### Made in Germany

HAZET No.		Output	S mm	Ø mm	EAN-No. 4000896+	
2169-14	125 1/2	14-point	72	103	244195	

### 1/2" oil filter wrench set

- For operating oil filters and oil filter housings
- Positive mounting of the oil filter housing
- · Required torque-controlled screw tightening is possible
- · For operation with
  - 2169-12: Oil filter in OPEL models Astra K, Insignia B with 1.5 diesel engines F15DVC, F15DVH with 77KW / 90KW
  - 2169-13: For operations of the oil filter in HYUNDAI i30, Tucson KIA Ceed, Sportage, Soul, Stonic with 1.6 CRDI engine
  - 2169-8A: For operation of the oil filter in FORD models e.g. with EcoBoost engines incl. B-Max; C-Max 2; Fiesta 5-6-7; Focus 2-3; Fusion; Galaxy; Mondeo 4-5; Tourneo; Transit, Ka+; Kuga 2; S-Max MAZDA 2 (DL, DJ) 1.5D; 3 (BK, BL) 2.0 (BM, BN) 1.5D - 2.2D (BP) 1.8D; 5 (CW) 1.8-2.0; 6 (GG) 1.8-2.0 (GY, GH) 1.8-2.0-2.5 (GJ, GL) 2.2D; CX-3 (DK) 1.5D-1.8D; CX-5 (KE,GH,KF) 2.2D; CX-7 (ER) 2.3D-2.5D; MX-5 (NC) 1.8-2.0

#### **Contents:**

2169-12



#### 2169/3

EAN-No. 4000896241989





#### Oil filter wrench, individual

#### Made in Germany

HAZET No.		Output	S mm	Ø	EAN-No. 4000896+	
2169-12	125 1/2	15 grooves	74.7	107	241798	
2169-13	125 1/2	14-point	80	92	241859	
2169-8A	125 1/2	15-point	74	105	232956	

### 1/2" oil filter wrench

- ullet Operation of a Purflux oil filter with  $\varnothing$  76 mm and 12 grooves
- · With protective coating
- For e.g. AUDI, CITROEN, DACIA, FIAT, FORD, MERCEDES-BENZ, NISSAN, PEUGEOT, RENAULT, HONDA, OPEL/VAUXHALL, SUZUKI, VW, SEAT,
- . In various RENAULT engines, e.g. K9K engines, the oil filter is located very close to the alternator or starter
- Danger: A short circuit can occur here when using a standard oil filter wrench
- Outside hexagon 24 mm / s 76 mm groove profile (6 grooves)



Made in Germany

2169-76B

EAN-No. 4000896230259




### **Fuel filter releasing tool**

- Can be used easily even in areas with restricted access
- · For operating the fuel filter housing when changing the fuel filter cartridge on FORD Duratorg 2.2 TDCl engines, Transit Custom since  $04/2012 \rightarrow$ , Tourneo Custom since  $04/2012 \rightarrow$ ,

Transit since 08/2013

- Output: groove profile
- Length: 130 mm
- Outside Ø: 160 mm



Made in Germany 2168-2

EAN-No. 4000896226870

### **FORD** socket for plastic oil drain plug

- Perfectly designed for plastic oil drain plugs
- · Prevents damage resulting from the use of e.g. unsuitable extraction tools
- · Special socket for operating the plastic oil drain plug for e.g. CITROËN C4, C5, Spacetourer, Jumpy, DS4, DS5 with 2.0 Blue HDi engine

model year 09.2013 →; **FORD** Mondeo, S-Max, Kuga, Galaxy, Focus, C-Max with 2.0 TDCi engine model year 09.2014

FORD (USA) Edge with 2.0 TDCi engine model year 08.2015 -

FORD (Australia) Kuga, Escape, Mondeo with 2.0 TDCi engine model year 09.2014  $\rightarrow$ ; **OPEL** Grandland X 2.0 D model year 11.2017  $\rightarrow$ ; **PEUGEOT** 308, 508, 3008, 5008, Expert, Traveller with 2.0 Blue HDi engine model year 11.2013 →; **TOYOTA** Proace Verso, bus, van, platform with 2.0 D engine model year 02.2016 → OPEL/VAUXHALL Grandland X 2.0 D

model year 10.2017 →

· Lenath: 32 mm





EAN-No. 4000896224159



### **Engine**



### **Unlocking tool for VAG plug connections**

 For non-damaging unlocking of electrical connections on various components and sensors such as injectors, rail pressure sensors, fluid level sensors, ignition coils, vacuum sensors, brake wear sensors, pressure regulators, lighting systems and various other connectors of the VAG group












Extra-long blade, curved at the head, allows access to hard-to-reach places!









#### Made in Germany

HAZET No.	Blade length (mm)	Head offset (mm)	[ mm	EAN-No. 4000896+	
4675-1	71	_	130	244331	
4675-2	132	20	191	244348	

Available in April 2022!

### Pipe stopper set

- Very quick closure of pipes prevents liquids from escaping
- For sealing pipelines in brake systems, air conditioning systems, power steering and fuel systems that cannot be secured with a flexible hose clamp
- For single sealing in sizes of 6.3 mm ( $^{1}/_{4}$ ") · 8 mm ( $^{5}/_{16}$ ") · 10 mm ( $^{3}/_{8}$ ") and for double sealing (e.g. banjo connections) in size 10 mm ( $^{3}/_{8}$ ")



#### 4591/4

EAN-No. 4000896219650



1965/2

4

EAN-No. 4000896**223008** 



Universal hook/wedge set

• Plastic wedge: length 214 mm, width 26.5 mm

door seals, carpets, interior trim

· Universal hook: length 180 mm

• For loosening components such as e.g. door clips as

well as for lifting and alignment work, window rubber,




### Brakes



### 1/2" brake calliper screwdriver socket

- Problem-free operation of the brake calliper screw connection
- Brake calliper screw connection on: e.g. MERCEDES-BENZ ML-Class, Type 166, model years 2011 →, FORD Mondeo model years 2014 →,
- C-Max, S-Max and Galaxy model years 2015 →





### Square brake calliper file

- Extra slim design
- For easy removal of stubborn brake dust, rust and dirt from the brake calliper



### **Brake line scraper**

- Curved design enables work even in cramped and hard-to-reach areas
- · For removing dirt, underbody protection and rust from brake lines and for locating concealed corrosion areas
- . Application is possible with pulling or pushing
- Replaceable blade
- For brake line Ø 4.75 mm
- Length: 245 mm

## Made in Germany HAZET No. Designation EAN-No. 4000896 + 4968-12 Brake line scraper 219964 4968-012 Replacement blade for brake line scraper 4968-12 229871




### Calliper gauge for brake discs / thickness gauge


- Measurement without wheel removal
- Effortless measurement on the vehicle in the course of direct receptions in the presence of the customer
- Measuring range: 0 60 mm (also suitable for application on commercial vehicles)
- Easy to handle
- Length: 395 mm
- Note: Information on the wear limits Please observe vehicle manufacturer's data!



### Calliper gauge for brake discs / diameter

- Simple, quick determination of the brake disc diameter through wheel opening without removing the wheels
- For determining the brake disc diameter through rim openings
- Measuring range: 200-400 mm





### **Brakes**



### Brake piston readjusting tool set, pneumatic 4

- Universal application due to new 3-piece adapter set as well as optimisation of the HAZET basic unit 4970P-1
- Now also permits use with brake pistons that are extended further
- · Suitable for clockwise and anti-clockwise brake pistons
- · Pneumatic support together with swivelling rotary level allows effortlessly easy and
- It is possible to simultaneously press and turn or only press the brake piston after the brake pads on disc brake systems have been replaced
- Incl. case with soft-foam insert and storage options for additional adapters as well as operating instructions

#### **Contents:**

- Basic unit: 4970P-1
- Adapter set: 4970P-02/3, 3 pieces








other manufacturers available on the market, e.g: 1) Inside hexagon adapter s 13 mm for HAZET adapter of group 4970

- or adapter set 4970/5
- 2 10 mm  $^3/_8$ " outside square adapters to connect OEM special adapters e.g. all current MINI and BMW adapters, BMW 1 series up to BMW X5 brake callipers (current largest calliper), SW-Stahl
- 3 2-pin adapters e.g. for VIGOR, SW-Stahl, KS-Tools, Facom, BGS, Kunzer

#### 12,91(%)

### Maximum possible return movement of the piston rod into the housing

Application is now also possible with small brake callipers, e.g. on MINI and BMW 1 series  $\rightarrow$  X5, and even with particularly widely extended brake pistons





4970P-1/4

EAN-No. 4000896232970

### **Adapter set**

- Universal application for numerous vehicles
- Please consider manufacturer's data and brake calliper design

Suitable for use with 4970P-1/4 and 4970-1





4970-5



4970-6



4970-7



4970-8



Made in Germany 4970/5 EAN-No. 4000896235544

Also see tool catalogue 2022, page 423







### Body | Chassis

### Universal spreader for wheel bearing housing (mechanical)


- Expansion of the spring strut and ball joint mounting (separating the spring strut from the wheel bearing housing)
- · Large spreading range enables universal use
- For manual operation

- · Output: parallel pressure surfaces
- Spreading range: 5.0-11.5 mm
- Counterhold with s 17 mm possible
- Easy handling: parallel pressure surfaces prevent the tool from accidentally popping out or slipping off





Made in Germany	
4912-5	
EAN-No. 4000896239900	
	W





8 5/16 0 0 5

### 5/16" door hinge screwdriver bit set

- Plug connection 9 x 12 mm square
- All VW, AUDI, SEAT, ŠKODA door hinge screwdriver bits in one set
- Torque-controlled screw tightening possible (Please follow the instructions of the manufacturer)
- Installing, removing and adjusting the driver and passenger door: Removing or loosening together with tool holder HAZET 6396
  - Installation with torque wrench HAZET 6290-1CT or 5290-3CT
- · For operation with
- 2597-01: **VW, ŠKODA** Fabia 2 model year 2007  $\rightarrow$  2014, Roomster model year 2006  $\rightarrow$  2015, **AUDI** A5 model year  $2007 \rightarrow 2016$
- 2597-02: **VW** Golf 4 model year 1997  $\rightarrow$  2006, Golf 7 model year 2012  $\rightarrow$  2021, Passat B5 model year  $1996 \rightarrow 2000$ , **SEAT** León model year  $1999 \rightarrow 2006$
- -2597-03: **VW** Golf 5 model year 2003  $\rightarrow$  2008, Golf 6 model year 2008  $\rightarrow$  2012, Passat B6 model year 2005→2010,

Caddy model year 2004  $\rightarrow$  2010, Beetle model year 2011  $\rightarrow$  2019, Sharan 2 model year 2010  $\rightarrow$ , Tiguan model year 2011  $\rightarrow$ , Touran model year 2010  $\rightarrow$ , **ŠKODA** Superb model year 2008  $\rightarrow$ 

2597-04: VW Polo 6 model year 2017→, T-Cross model year 2018, ŠKODA Fabia 3 model year 2014→, PORSCHE Panamera

– 2100-02: For replacing the screwdriver bits and operating the inside hexagon

#### **Contents:**

- 2597 door hinge insert tool, incl. screwdriver bit T45 TORX®
- 2597-02 screwdriver bit (XZN) M10
- 2597-03 screwdriver bit (XZN) M8
- 2597-04 screwdriver bit (XZN) M12
- 2100-02 offset screwdriver

### Made in Germany

2597-2/5

EAN-No. 4000896242122



### Door hinge screwdriver bit

Output size: M12

Length: 22 mm



Made in Germany

Actual size

### 2597-04 EAN-No. 4000896241972

### 3/8" clamp pliers for axle boots

 For installing axle boots made of Hytrel and bands made of special stainless steel with pre-set torque values, in conjunction with e.g. torque wrench



### Sliding hammer

- M 16 x 1.5
- Striking weight: 1.8 kg
- Length: 460 mm

Suitable for use with 4935-11/12



Made in Germany 4797-1

EAN-No. 4000896121175





### Chassis | Cardan shafts

### **Circlip pliers set**

- Easier, damage-free assembly of the drive shaft joint: Damage to the serration of joint and shaft is avoided with internal circlip during assembly of the drive shaft joint
- · Correct, centred insertion of the circlip when mounting the joint on the drive shaft
- Easy fixing of the locking pliers over the circlip without damaging the bellows
- . The pliers automatically slip down when striking the joint
- Suitable for drive shafts from all manufacturers

#### **Contents:**

- Circlip pliers 1847-12
- 7x pairs of half shells in graduated diameter sizes:
- Half shells Ø: 19 · 21.4 · 22.3 23 · 23.8 24.6 ·  $26.2 - 26.9 \cdot 28.5 - 29.2 \cdot 30 \text{ mm}$







Supplement:

### Half shell pair

- Supplement for HAZET circlip pliers set 1847-12/15
- · Easy, damage-free installation of the drive shaft joint on VW T5/T6
- Half shell pair: Ø 32.8 mm







Made in Germany 1847-128/2 EAN-No. 4000896242009

### Drive shaft disassembly / assembly set

- For disconnecting the drive shaft joint and pulling in the shaft through the wheel hub with just
- Disconnecting the drive shaft joint from the shaft using the sleeves or spindles together with e.g. HAZET sliding hammer 4797-1 (not included in delivery)
- · Pulling in the drive shaft through the wheel hub on vehicles where the drive shaft is very difficult to pull through the wheel hub
- · Suitable for all vehicle brands
- For drive shafts with outside and inside thread

### **Contents:**

- 2x spindles (M14, M16) for pulling the drive shaft through the wheel hub or separating the joint from the drive shaft when the joint has an inside thread
- 2x sleeves for support on the wheel hub
- Spindle nut
- 7x screw sleeve adapters
- XX SCRW SIGEVE AGAPTERS
   M16 x 1.5 (VAG, MAZDA)
   M18 x 1.5 (VOIVO, SUZUKI, OPEL/VAUXHALL)
   M20 x 1.5 (MERCEDES-BENZ, VAG, MITSUBISHI, MAZDA)
   M22 x 1.5 (FIAT, PSA, BMW, FORD, OPEL, HYUNDAI)
   M24 x 1.5 (RENAULT, BMW, MERCEDES-BENZ, OPEL/VAUXHALL, MAZDA, HONDA, VAG)
   M27 x 1.5 (PSA, BMW, FORD)
   M30 x 1.5 (MERCEDES-BENZ, PSA, BMW)













### Universal inside spring vice set, 6 pieces

- Removal and installation of the coil spring on the rear axle
- Innovative anti-rotation device for lower tensioning jaws integrated in the base component reduces the outer diameter to only Ø 32 mm thanks to compact design
- Pendulum hexagonal head for equal force distribution with integrated anti-rotation protection for upper tensioning jaws
- One-sided counterholder for the spindle made possible by hexagon on top, e.g. with combination wrench HAZET 600 N-13
- For removal and installation of springs with small coil spacing, e.g. for the MINI Cooper S
  (third generation) · VW Passat (B8)
- Extension of the span to 120 mm and an increase of the maximum load for increasing vehicle weights (electric and hybrid vehicles), for safe working up to 31,000 N → Tested with at least four-fold safety against breakage (GS mark of tested safety)
- 17° angular movement of the tensioning jaws now ensures removal of C-shaped (bent) springs, e.g. on the AUDI A4 (B9) · VW Golf 7
- Internal and external guidance of the tensioning jaws prevents the spring from sliding out
- · All tensioning jaws included, reusable replaceable plastic protective pads

#### **Contents:**

- Inner spring vice 4904-1 (spindle, drive nut, pressure sleeve with anti-rotation device)
- Tensioning jaw 4904-10 · span width 64 115 mm
- Tensioning jaw 4904-11 · span width 64 115 mm
- Tensioning jaw 4904-12  $\cdot$  span width 79.5 133 mm
- Tensioning jaw 4904-13 · span width 79.5 133 mm
- Tubular box wrench 4902-224 · s 24 mm

# Universal application on almost all passenger cars!

# Tested on vehicles from the following manufacturers:

AUDI · BMW · CITROËN · FIAT · FORD ·

HYUNDAI · KIA · MAZDA ·

MERCEDES-BENZ · MINI · OPEL ·

PEUGEOT · RENAULT · SEAT · ŠKODA ·

TOYOTA · VOLKSWAGEN

# Only 202 mm long!

















### Chassis








Anti-rotation device

Clamping and counterholding





### **Highlights:**

- > Easy handling for just one user
- > Eliminates time-consuming work associated with most spring removal:
  - Removal of axle parts unnecessary
  - Axle alignment no longer necessary
  - Removal and installation possible in just a few minutes on each side

Conclusion: Compact HAZET design enables spring replacement on many vehicles with remarkable time savings!

> Made in Germany 4904/6 EAN-No. 4000896238897


### Support device for multi-link axle

- Universal application for nearly all vehicles
- Protective pads prevent damage to the vehicle parts
- Facilitates removal of rear axle springs
- Application in conjunction with 4904/6
- Clamping range: 80 127 mm Pressure piece diameter: Ø 30 mm
- · Safety: visual chain provides a reminder for tool removal
- Chain length: 750 mm



**Prevents unwanted raising of the chassis during a spring tensioning** process!







Made in Germany 4912-6

EAN-No. 4000896238835

PORSCHE

MOTORSPORT





### Chassis

4

### Stationary universal spring vice

### New seating and assembly concept

- Swivelling in horizontal or vertical working position
- HAZET recommendation for ergonomic working height: adjust vertically, operate horizontally
- Damage to shock absorbers and head plates impossible (no overload risk)
- Simple, lockable strut mount

#### **High safety**

- · Consistently reliable mounting of head plates
- Thread damage to piston rod impossible
- · Permanent fixation of spring throughout operation

# Secure investment by using existing components of SYSTEM 4900


- Existing basic units 4900-2A and all tensioning jaws of System 4900 may be used
- Use of future applications is assured

#### Allows record keeping by scaling

- If recurring, significant time savings by scaling
- Firm fixation eliminates readjustment at the same spring strut (left / right)

#### Can be used for almost any spring strut/shock absorber


Load-free disassembly / assembly with completely relieved shock absorber







Spring strut fixation





EAN-No. 4000896180561

N-No. 4000896180561

Application video 4903/4

Application video 4903/4 W 203










### Chassis











Optionally with reversible ratchet, cordless screwdriver or air ratchet without activating impact function

Swivelling Optimum working height approx. 1.30 m



# Safety spring vice set • Suitable for impact wrenches

- Closed system maintenance-free
- Variable system thanks to easily replaceable tensioning jaws
   With socket rail for machinist's vice
- No further special tool necessary
- Suitable for approx. 100 different vehicle types
- Contents:
  - Basic unit 4900-2A
  - 4x tensioning jaws each 2 x 4900-11 and 4900-12









Made in Germany 4900-2A/5 EAN-No. 4000896**086054** 







Das Werkzeug



163-172x50





163-515/16

**Tool trolley with** 378 expert tools

Stainless steel work surface

179NXXL-8 Made in Germany  $H \times W \times D$ 1,020 x 1,133 x 518 mm

163-478/40 🔘 🗨 🗇 2





163-380/4

163-527/56 ♦ ♦ ♦ ○ ○





163-382/3

163-479/26 € ○ ○ ○





Your HAZET specialist dealer



Assistent®





Made in Germany				
HAZET No.	Number of drawers			
179NXXL-7	7			
179NXXL-8	8			



2128N-1



Copyright 2022 © HAZET-WERK Hermann Zerver GmbH & Co KG Güldenwerther Bahnhofstraße 25–29, D-42857 Remscheid, Germany