

**Cleco**<sup>®</sup>  
Production Tools

**CellCore**<sup>™</sup>  
Cordless Assembly Tools

**EASY TO HANDLE. HARD TO BREAK.**



**THE SMARTEST TOOL FOR THE TOUGHEST ENVIRONMENT**

## CellCore™ puts you in control with cordless assembly tools that are **easy to handle**, and **hard to break**.

Cleco's new CellCore™ Cordless Assembly Tools are smart, durable and designed to withstand the toughest environments. The lightweight ergonomic design reduces operator fatigue while delivering state-of-the-art power, weight and balance. A large user interface makes it quick and easy to program rundowns on the tool without a controller.



**Durable** - Assembly line tough  
(Drop tested up to 5 feet)



**Reliable** - Increases uptime with 500k cycles  
between maintenance



**Ergonomic** - Reduces operator fatigue while  
delivering state-of-the-art power and intelligence



**Easy to Use** - Large user interface allows easy  
on-the-tool programming without a controller

**EASY TO HANDLE. HARD TO BREAK.**



### **CellCore is the most versatile, easy-to-use cordless tool in the industry.**

Users can program up to 10 rundown strategies, called "FastApps", directly on the tool in standalone mode. Users can also pair CellCore tools with Cleco's new mPro200 controller. By pairing the devices, users can easily capture data in real time and program advanced rundowns within a much more compact footprint.

## THE SMARTEST TOOL FOR THE TOUGHEST ENVIRONMENT

**Multi-Color LED** - Color worklight on the tool for secondary okay/not okay visual feedback

**Large User Interface** - Allows easy on-the-tool programming without a controller

**10 "Fast Apps" Programmable Rundown Strategies**

**Versatile** - Forward and backward compatibility with Cleco's entire Global Controller platform

**Exceptional Low Weight, Balance and Grip** - For superior ergonomics that increase productivity

**Increased Storage** - No uploading rundowns for up to one week (storage for 15,000 rundowns, 500 traces)

**"Stay Alive" Function** - Prevents reboot during battery change, gaining time and efficiency

### mPro200 Controller



#### 10 Tools. 1 Controller. Period.

The mPro200 Controller can be connected to 10 Cleco cordless tools. Easily capture and communicate data in real time within a plant network. Connect to the controller via mPro remote or external monitor.

**Compact** - Save space on the line (4.5" wide)

**Intelligent** - 19 fastening strategies for all types of applications

**Easy to Use** - Run remotely via mPro remote, or connect an external display using VGA output

**Increase Uptime** - Swap controllers quickly with interchangeable CompactFlash card

**Versatile** - Compatible with CellCore, LiveWire and I-Wrench

## PISTOL



MODEL NUMBER	TORQUE RANGE (Nm) Min-Max	TORQUE RANGE (ft-lb) Min-Max	SPEED r/min	WEIGHT* kg (lb)	LENGTH mm (in)	SIDE TO CENTER mm (in)	HEIGHT mm (in)	OUTPUT
CCBPW04Q	1.2 - 4	0.9 - 2.9	2480	0.98 (2.16)	185 (7.27)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW12Q	3.6 - 12	2.7 - 8.8	800	1.05 (2.32)	201 (7.89)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW123	3.6 - 12	2.7 - 8.8	800	1.05 (2.32)	198 (7.79)	29 (1.14)	204 (8.03)	3/8" Square Drive
CCBPW22Q	6.6 - 22	4.9 - 16.2	430	1.05 (2.32)	201 (7.89)	29 (1.14)	204 (8.03)	1/4" Hex Quick Change
CCBPW223	6.6 - 22	4.9 - 16.2	430	1.05 (2.32)	198 (7.79)	29 (1.14)	204 (8.03)	3/8" Square Drive

\*weight values do not include battery

## RIGHT ANGLE



MODEL NUMBER	TORQUE RANGE (Nm) Min-Max	TORQUE RANGE (ft-lb) Min-Max	SPEED r/min	WEIGHT* kg (lb)	LENGTH mm (in)	SIDE TO CENTER mm (in)	HEIGHT mm (in)	OUTPUT
CCBAW153	4.5 - 15	3.3 - 11.0	570	1.70 (3.75)	456 (17.95)	31.8 (1.25)	88 (3.46)	3/8" Square Drive
CCBAW253	7.5 - 25	5.5 - 18.4	305	1.70 (3.75)	456 (17.95)	31.8 (1.25)	88 (3.46)	3/8" Square Drive
CCBAW353	10.5 - 35	7.7 - 25.8	255	1.95 (4.30)	486 (19.15)	31.8 (1.25)	92 (3.63)	3/8" Square Drive
CCBAW503	15 - 50	11.1 - 36.8	165	2.00 (4.41)	499 (19.65)	31.8 (1.25)	92 (3.63)	3/8" Square Drive

\*weight values do not include battery

## CONTROLLERS†



MODEL NUMBER	DESCRIPTION	TOOL COMPATIBILITY	WEIGHT kg (lb)	WIDTH mm (in)	HEIGHT mm (in)	DEPTH mm (in)
mPro200GC	Controller	CellCore, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-AP	Controller with Access Point	CellCore, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-G	Controller (Global)	CellCore, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)
mPro200GC-AP - G	Controller with Access Point (Global)	CellCore, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)

†also compatible with the mPro400 Global Controller Platform

## ACCESSORIES



MODEL NUMBER	DESCRIPTION
T50-1000497	18V, 2.0Ah Battery (.43kg/.94lb)
T50-1000498	18V, 5.0Ah Battery (.72kg/1.60lb)
T50-1000499	18V Rapid Charger (NA)
T50-1000500	18V 6-Bay Sequential Charger (NA)
T50-1000506	18V Rapid Charger (Europe, Middle East, Africa)
T50-1000507	18V Charger (Brazil)
T50-1000508	18V 6-Bay Sequential Charger (Europe, Middle East, Africa)
T50-1000543	18V Charger (Argentina)
T50-1000544	18V Rapid Charger (United Kingdom)
T50-1000545	18V Rapid Charger (China)
T50-1000546	18V Rapid Charger (Japan)
T50-1000547	18V 6-Bay Sequential Charger (United Kingdom)

### The Americas

Apex Tool Group  
670 Industrial Drive  
Lexington, SC 29072  
USA  
Tel.: +1 (800) 845 5629  
Tel.: +1 (919) 387 0099  
Fax: +1 (803) 358 7681  
[www.ClecoTools.com](http://www.ClecoTools.com)

Apex Tool Group  
Manufacturing México  
S. de R.L. de C.V.  
Vialidad El Pueblito #103  
Parque Industrial Querétaro  
Querétaro, QRO 76220  
México  
Tel.: +52 (442) 211 3800  
Fax: +52 (800) 685 5560

Apex Tool Group  
Ind. Com. Ferram. Ltda. Av.  
Liberdade, 4055  
Zona Industrial Iporanga  
Sorocaba, São Paulo  
CEP# 18087-170  
Brazil  
Tel: +55 15 3238 3870  
Fax: +55 15 3238 3938

### Europe | Middle East | Africa

Apex Tool Group GmbH  
Industriestraße 1  
73463 Westhausen  
Germany  
Tel.: +49 (0) 73 63 81 0  
Fax: +49 (0) 73 63 81 222  
[www.ClecoTools.de](http://www.ClecoTools.de)

Apex Tool Group SAS  
25 Avenue Maurice Chevalier  
77330 Ozoi-La-Ferrière  
France  
Tel: +33 16 44 32 200  
Fax: +33 16 44 317 17

Apex Tool Group  
Hungária Kft.  
Pálfarfai u.2  
9027 Győr  
Hungary  
Tel.: +36 96 66 1383  
Fax: +36 96 66 1135

### Asia Pacific

Apex Power Tool Trading  
(Shanghai) Co., Ltd.  
2nd Floor, Area C  
177 Bi Bo Road  
Pu Dong New Area, Shanghai  
China 201203 P.R.C.  
Tel.: +86 21 60880320  
Fax: +86 21 60880298

Apex Power Tools India  
Private Limited  
Gate No. 1, Plot No. 5  
S. No. 234, 235 & 245  
Indialand Global Industrial Park  
Taluka-Mulsi, Phase I  
Hinjawadi, Pune 411057  
Maharashtra, India  
Tel.: +91 020 66761111